

[54] BATTERY CHARGER MOUNTING BRACKET

2,892,927	6/1959	Rosenblum	248/300
3,599,921	8/1971	Cumber	248/300
4,335,863	6/1982	Rapps	D8/382

[76] Inventor: Ranjit Dey, 2465 Dunwin Drive, Unit 11, Mississauga, Ontario, Canada, L5L 1T1

[**] Term: 14 Years

[21] Appl. No.: 616,234

[22] Filed: Jun. 1, 1984

[52] U.S. Cl. D8/73; D8/366

[58] Field of Search D8/373, 363, 382, 354, D8/371, 380, 366; 248/300; D13/5, 6, 10

[56] References Cited

U.S. PATENT DOCUMENTS

D. 122,945	10/1940	Quirk	D13/6
D. 184,600	3/1959	Carlson	D8/373
D. 255,323	6/1980	Polinroth	D8/373
D. 262,284	12/1981	Caron	D13/10
D. 270,574	9/1983	Black	D8/354
D. 280,800	10/1985	Chalberg	D8/380
2,681,164	6/1954	Kalfen	248/300
2,873,301	3/1959	Dierstein et al.	248/300

OTHER PUBLICATIONS

Dahlstrom Metal Shapes etc; catalog No. 11, Angles as shown in sections 1 and 7.

Ainsworth Mfg. Corp.; Multi-A-Frame Div.; catalog; at p. 15; item F-4302(1-7).

Amer. Instit. of Architects; Romsey/Sleeper; Architectural Graphic Standards; 7th ed.; chapter 5 Metals.

Primary Examiner—James M. Gandy

Assistant Examiner—Horace B. Fay

[57] CLAIM

The ornamental design of a battery charger mounting bracket, as shown and described.



DESCRIPTION

FIG. 1 is a front perspective view of a battery charger mounting bracket showing my new design;

FIG. 2 is a right side elevational view thereof, the side opposite being a mirror image;

FIG. 3 is a top plan view thereof; and

FIG. 4 is a front elevational view thereof.






FIG. 3




FIG. 1




FIG. 2




FIG. 4