

[54] COMBINED PATCH FOR DAMAGED WALLS AND DOOR BUMPER

D. 265,457	7/1982	Littlefield	D8/350
2,899,703	8/1959	Johnson	16/86 A
3,050,770	8/1962	Morse et al.	16/86 A
3,484,891	12/1969	Borgen	16/86 A
3,864,785	2/1975	Hoppock	16/86 A

[76] Inventor: Steve R. Angle, 5824 S. Jordan Canal Rd., Salt Lake City, Utah 84118

[**] Term: 14 Years

Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—Thorpe, North & Western

[21] Appl. No.: 670,770

[57] CLAIM

[22] Filed: Nov. 14, 1984

The ornamental design for a combined patch for damaged walls and door bumper, substantially as shown and described.

[52] U.S. Cl. D8/400; D8/350; D8/402

[58] Field of Search D8/350, 402, 400; 16/82, 86 R, 86 A, 86 B; D6/300; D11/132


DESCRIPTION

[56] References Cited

FIG. 1 is a front elevational view of a combined patch for damaged walls and door bumper showing my new design, the rear being unornamented; FIG. 2 is a side elevational view thereof, all sides being identical.

U.S. PATENT DOCUMENTS

D. 257,123 9/1980 Farmer, Jr. D8/402






Fig. 1




Fig. 2