United States Patent [19]

Armstrong et al.

[11] Patent Number: Des. 289,328

[45] Date of Patent: ** Apr. 14, 1987

[54] ORTHODONTIC APPLIANCE ACCESSORY

[75] Inventors: Maclay M. Armstrong, Seattle;

Steven A. Houser, Edmonds; Jeffrey A. Armstrong, Mercer Island, all of

Wash.

[73] Assignee: Unitek Corporation, Monrovia, Calif.

[**] Term: 14 Years
[21] Appl. No.: 859,874

[22] Filed: May 2, 1986

Related U.S. Application Data

[63] Continuation of Ser. No. 834,288, Feb. 27, 1986, which is a continuation-in-part of Ser. No. 609,409, May 11, 1984.

[56] References Cited

U.S. PATENT DOCUMENTS

3,497,954	3/1970	Kesling 433/13
4,443,189	4/1984	Wildman 433/13 X

OTHER PUBLICATIONS

Unitek Catalogue #112 (1962), p. 21—item "F", Split Round Tube Hook—Class 433, Searchroom Catalogue Collection.

Primary Examiner—Wallace R. Burke Assistant Examiner—Brian N. Vinson Attorney, Agent, or Firm—Robert W. Beach; Ward Brown

[57] CLAIM

The ornamental design for an orthodontic appliance accessory, as shown and described.

DESCRIPTION

FIG. 1 is a top front perspective view of an orthodontic appliance accessory seen obliquely from the right side showing our new design;

FIG. 2 is a top rear perspective view thereof seen obliquely from the left side;

FIG. 3 is a top rear perspective view thereof seen obliquely from the right side;

FIG. 4 is a top front perspective view thereof seen obliquely from the left side;

FIG. 5 is a rear end elevation view thereof;

FIG. 6 is a front end elevation view thereof;

FIG. 7 is a side elevation view thereof seen from the left of FIG. 6;

FIG. 8 is a side elevation view thereof seen from the right of FIG. 6;

FIG. 9 is a top plan view thereof;

FIG. 10 is a bottom plan view thereof;

FIG. 11 is a top front perspective view of a second embodiment thereof seen obliquely from the right side; FIG. 12 is a top rear perspective view of the second embodiment thereof seen obliquely from the right side; FIG. 13 is a top rear perspective view of the second embodiment thereof seen obliquely from the left side; FIG. 14 is a top front perspective view of the second embodiment thereof seen obliquely from the left side; FIG. 15 is a rear end elevation view of the second embodiment thereof;


FIG. 16 is a front end elevation view of the second embodiment thereof;


FIG. 17 is a side elevation view of the second embodiment thereof seen from the right of FIG. 16;

FIG. 18 is a side elevation view of the second embodiment thereof seen from the left of FIG. 16;

FIG. 19 is a top plan view of the second embodiment thereof; and

FIG. 20 is a bottom plan view of the second embodiment thereof.





•

.

Fig.1.




Fig. 2.




Fig. 3.







Fig. 4










Fig.5.

Fig. 7.

Fig. 8.

Fig. 6.




Fig. 9.




Fig. 10.

U.S. Patent Apr. 14, 1987 Sheet 2 of 2 Des. 289,328




Fig. 19.

•

Fig. 20.

•