

[54] BUCKLE

[76] Inventor: Kazumi Kasai, 3105-1, Kamikoizumi, Namerikawa-shi, Toyama-ken, Japan

[**] Term: 14 Years

[21] Appl. No.: 720,343

[22] Filed: Apr. 5, 1985

[30] Foreign Application Priority Data

May 7, 1984 [JP] Japan D59-18612

[52] U.S. Cl. D11/216

[58] Field of Search D11/200, 201, 208, 216, D11/218, 220; 63/2; 24/163 R, 163 K, 170, 307-314, 323, 644, 650, 651, 171, 196

[56] References Cited

U.S. PATENT DOCUMENTS

D. 264,766	6/1982	Huff	D11/216
4,150,464	4/1979	Tracy	24/313
4,282,634	8/1981	Krauss	24/323
4,604,772	8/1986	Arff	24/311 X

Primary Examiner—Louis S. Zarfes
Attorney, Agent, or Firm—Hill, Van Santen, Steadman & Simpson

[57] CLAIM

The ornamental design for a buckle, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a buckle showing my new design;
 FIG. 2 is a rear elevational view of the buckle of FIG. 1;
 FIG. 3 is a plan view of the buckle;
 FIG. 4 is a bottom view of the buckle;
 FIG. 5 is a right-side-elevational view of the buckle;
 FIG. 6 is a cross-sectional view taken along line A—A of FIG. 1;
 FIG. 7 is a front elevational view of the male member of the buckle;




FIG. 8 is a rear elevational view of the male member of the buckle;
 FIG. 9 is a plan view of the male member of the buckle;
 FIG. 10 is a bottom view of the male member of the buckle;
 FIG. 11 is a right-side-elevational view of the male member of the buckle;
 FIG. 12 is a cross-sectional view taken along line B—B of FIG. 7;
 FIG. 13 is a front elevational view of the anchoring seat for the male member;
 FIG. 14 is a rear elevational view of the anchoring seat for the male member;
 FIG. 15 is a plan view of the anchoring seat for the male member;
 FIG. 16 is a right-side-elevational view of the anchoring seat for the male member;
 FIG. 17 is a cross-sectional view taken along line E—E of FIG. 13;
 FIG. 18 is a front elevational view of the female member of the buckle;
 FIG. 19 is a rear elevational view of the female member of the buckle;
 FIG. 20 is a plan view of the female member of the buckle;
 FIG. 21 is a bottom view of the female member of the buckle;
 FIG. 22 is a right-side-elevational view of the female member of the buckle;
 FIG. 23 is a cross-sectional view taken along line C—C of FIG. 18;
 FIG. 24 is a cross-sectional view taken along line D—D of FIG. 20;
 FIG. 25 is a front elevational view of the anchoring seat for the female member;
 FIG. 26 is a rear elevational view of the anchoring seat for the female member;
 FIG. 27 is a plan view of the anchoring seat for the female member;
 FIG. 28 is a bottom view of the anchoring seat for the female member;
 FIG. 29 is a right-side-elevational view of the anchoring seat for the female member;
 FIG. 30 is a cross-sectional view taken along line F—F of FIG. 25.




FIG. 1




FIG. 2




FIG. 3





FIG. 4






FIG. 5




FIG. 6

FIG. 9




FIG. 7




FIG. 10




FIG. 8




FIG. 11




FIG. 12



FIG. 13




FIG. 14




FIG. 15




FIG. 16



FIG. 17



FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 23




FIG. 22




FIG. 24




FIG. 25




FIG. 26




FIG. 29



FIG. 27




FIG. 28




FIG. 30

