

[54] **COMBINED LATCH OPERATING HANDLE AND HANDLE HOUSING**

[75] **Inventors:** Lee S. Weinerman, Strongsville; Michael J. Rachocki, Brunswick, both of Ohio

[73] **Assignee:** The Eastern Company, Cleveland, Ohio

[**] **Term:** 14 Years

[21] **Appl. No.:** 601,651

[22] **Filed:** Apr. 18, 1984

[52] **U.S. Cl.** D8/302; D8/306

[58] **Field of Search** D8/300, 306, 301, 302; 70/207, 208; 292/194, 229, DIG. 31

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 218,672	9/1970	Lauper	D8/306
D. 230,132	1/1974	Pastva, Jr.	D8/306
2,686,687	8/1954	Singleton	287/93
2,874,986	2/1959	Henrechs	292/DIG. 31
3,044,815	7/1962	Soss	292/DIG. 31
3,055,204	9/1962	Pelcin	70/153
3,297,916	1/1967	Wright	317/100
3,584,483	6/1971	Orr	70/81
3,655,230	4/1972	Armstrong	292/169
3,782,141	1/1974	Doerrfeld	70/146
3,871,198	3/1975	Miller	70/146
4,038,718	8/1977	Reilhac et al.	16/110
4,300,794	11/1981	Dunsmoor	292/247
4,309,884	1/1982	Davis	70/472
4,578,968	4/1986	Messier, Jr.	70/208

OTHER PUBLICATIONS

Sweet's Architectural catalog file 1962; Sec. 16a/Kav; p. 5; Handle w/Striated Pattern C.
National Lock Hardware brochure and accompanying

General Electric drawings (data and author unknown) showing a Flush Panel Lock.


Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—David A. Burge

[57] **CLAIM**

The ornamental design for a combined latch operating handle and handle housing, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a combined latch operating handle and handle housing showing our new design; FIG. 2 is a front elevational view thereof; FIG. 3 is a left side elevational view thereof; FIG. 4 is a rear elevational view thereof; FIG. 5 is a right side elevational view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is a perspective view thereof with the handle in the open position; FIG. 9 is a front elevational view of FIG. 8; FIG. 10 is a left side elevational view of FIG. 8; FIG. 11 is a right side elevational view of FIG. 8; FIG. 12 is a top plan view of FIG. 8; FIG. 13 is a bottom plan view of FIG. 8; FIG. 14 is a front elevational view of a second embodiment of the design of FIG. 1, the only difference being the inclusion of the grooved pattern; FIG. 15 is an enlarged fragmentary sectional view taken in the direction of the arrows on line 15—15 of FIG. 14; FIG. 16 is an enlarged sectional view taken in the direction of the arrows on line 16—16 of FIG. 14; FIG. 17 is an enlarged sectional view taken in the direction of the arrows on line 17—17 of FIG. 14; FIG. 18 is a front elevational view of a third embodiment of the design of FIG. 1, the only difference being the omission of the square opening; FIG. 19 is a front elevational view of a fourth embodiment of the design of FIG. 1, the only differences being the omission of the square opening and the inclusion of the grooved pattern.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19