

[54] DENTAL TIP

[76] Inventor: William B. Dragan, 85 Burr St.,
Easton, Conn. 06612

[**] Term: 14 Years

[21] Appl. No.: 792,802

[22] Filed: Oct. 30, 1985

[52] U.S. Cl. D24/16

[58] Field of Search D24/4-5,
D24/10-16, 23-26, 29, 45, 55, 59-60, 63;
D32/17-18, 21, 25, 31-32; D9/373, 302, 338,
434-435, 445, 447, 449; 433/90, 89;
604/239-240, 257, 264, 275; 222/326; D8/14.1;
D7/43, 48, 52, 68, 397-398

[56] References Cited

U.S. PATENT DOCUMENTS

D. 35,335	11/1901	Luff	D23/34
D. 177,796	5/1956	Collins	D23/34
D. 218,824	9/1970	Lawrence, Sr.	D23/34
D. 224,655	0/1972	Dragan	D24/99
2,754,033	7/1956	Etter	222/326
3,436,828	4/1969	Dragan	D24/14
3,581,399	8/1971	Dragan	433/90
3,900,954	8/1975	Dragan	433/90
4,391,590	5/1983	Dougherty	433/90

OTHER PUBLICATIONS

Spraying Systems Co. Catalogue (1963) p. 23 "Blow-Off Nozzle, Type 1/4TT.

Primary Examiner—Wallace R. Burke

Assistant Examiner—Brian N. Vinson

Attorney, Agent, or Firm—Arthur T. Fattibene

[57] CLAIM

The ornamental design of a dental tip, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a dental tip wherein my new design is embodied in a nozzle;
FIG. 2 is a left side elevational view thereof, the right side being a mirror image;
FIG. 3 is a top plan view thereof;
FIG. 4 is a bottom plan view thereof;
FIG. 5 is a rear elevational view thereof;

FIG. 6 is a front elevational view thereof;

FIG. 7 is a rear elevational view thereof, shown in an open position;

FIG. 8 is a top perspective view of a second embodiment thereof, wherein my design is embodied in a combined nozzle and cap therefor;

FIG. 9 is a left side elevational view of the embodiment of FIG. 8, the right side being a mirror image;

FIG. 10 is a top plan view of the embodiment of FIG. 8;

FIG. 11 is a bottom plan view of the embodiment of FIG. 8;

FIG. 12 is a rear elevational view of the embodiment of FIG. 8;

FIG. 13 is a front elevational view of the embodiment of FIG. 8;

FIG. 14 is a rear elevational view of the embodiment of FIG. 8, shown in an open position;

FIG. 15 is a top perspective view of a third embodiment thereof, wherein my design is embodied in a nozzle;

FIG. 16 is a left side elevational view of the embodiment of FIG. 15, the right side being a mirror image;

FIG. 17 is a top plan view of the embodiment of FIG. 15, the bottom being identical in appearance;

FIG. 18 is a front elevational view of the embodiment of FIG. 15;

FIG. 19 is a rear elevational view of the embodiment of FIG. 15;

FIG. 20 is a rear elevational view of the embodiment of FIG. 15, shown in an open position;

FIG. 21 is a top perspective view of a fourth embodiment thereof, wherein my design is embodied in a nozzle;

FIG. 22 is a left side elevational view of the embodiment of FIG. 21, the right side being a mirror image;



FIG. 23 is a top plan view of the embodiment of FIG. 21, the bottom being identical in appearance;

FIG. 24 is a front elevational view of the embodiment of FIG. 21;

FIG. 25 is a rear elevational view of the embodiment of FIG. 21;

FIG. 26 is a rear elevational view of the embodiment of FIG. 21, shown in an open position; and

FIG. 27 is a reduced top perspective view of a fifth embodiment thereof, wherein my design is embodied in a combined nozzle and cap therefor, the only difference residing in the inclusions of a cap element.






FIG. 1




FIG. 5




FIG. 2




FIG. 6




FIG. 3




FIG. 7




FIG. 4










FIG. 11

