

[54] **ADAPTOR FOR A WIRE CHANNEL**
 [75] **Inventor: David W. Bramwell, Prestatyn, Wales**
 [73] **Assignee: EGA Limited, United Kingdom**
 [**] **Term: 14 Years**
 [21] **Appl. No.: 641,493**
 [22] **Filed: Aug. 15, 1984**
 [30] **Foreign Application Priority Data**
 Jun. 26, 1984 [GB] United Kingdom 1020642
 [52] **U.S. Cl. D13/13**
 [58] **Field of Search D13/13, 24-26, D13/28-31; 174/48, 68 R, 68 C, 98, 101; 138/156, 162, 163, 166, 168; 339/20, 21 R, 22 R, 23**

[56] **References Cited**
U.S. PATENT DOCUMENTS
 2,669,632 2/1954 Hammerly 339/21 R
 3,821,688 6/1974 Larsile 339/22 R
 3,871,730 3/1975 Hesse 339/21 R
 3,960,426 6/1976 Heritage 339/21 R
 3,980,368 9/1976 Fremont 339/21 R
 4,589,449 5/1986 Bramwell 174/101

Primary Examiner—Susan J. Lucas
Assistant Examiner—Clare E. Heflin
Attorney, Agent, or Firm—Andrus, Scales, Starke & Sawall

[57] **CLAIM**
 The ornamental design for an adaptor for a wire channel, as shown and described.

DESCRIPTION
 FIG. 1 is a front elevational view of the adaptor for a wire channel showing my new design;
 FIG. 2 is a top plan view thereof;
 FIG. 3 is a side elevational view thereof;
 FIG. 4 is a sectional view thereof taken along line 4—4 of FIG. 1;
 FIG. 5 is a sectional view thereof taken along line 5—5 of FIG. 1;
 FIG. 6 is a rear elevational view thereof;
 FIG. 7 is a bottom plan view thereof.
 The adaptor can be fitted on the end of a length of cable trunking and a box for electrical components secured thereto. The box would have an aperture corresponding to the aperture formed in the adaptor and is clipped on to the adaptor by means of three lugs arranged around the aperture in the adaptor.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

