

[54] STEAM IRON

[75] Inventors: Marshall B. Johnson; John C. Meadway, both of Chillicothe, Ohio

[73] Assignee: Wearever-Proctorsilex, Chillicothe, Ohio

[**] Term: 14 Years

[21] Appl. No.: 878,751

[22] Filed: Jun. 26, 1986

[52] U.S. Cl. D32/70

[58] Field of Search D32/68-73; 38/77.1-77.9

[56] References Cited

U.S. PATENT DOCUMENTS

D. 189,887	3/1961	Boldt .	
D. 214,753	7/1969	Schellers	D32/70
D. 235,128	5/1975	Eaton et al. .	
D. 240,997	8/1976	Julkenbeck .	
D. 246,629	12/1977	Hanson et al. .	
D. 247,088	1/1978	Hanson et al. .	
D. 247,089	1/1978	Hanson et al. .	
D. 247,090	1/1978	Hanson et al. .	
D. 262,771	1/1982	Hanson .	
D. 267,673	1/1983	Ernest et al.	D32/70
D. 268,216	3/1983	Leirn	D32/70
D. 269,213	5/1983	Martin	D32/70
D. 269,213	5/1983	Martin .	
D. 284,800	7/1986	Cavalli	D32/70
D. 285,133	8/1986	Bluestein	D32/70
D. 285,376	8/1986	Stutzer et al. .	
D. 286,215	10/1986	Pataki	D32/70

OTHER PUBLICATIONS

Brochure titled Proctor Silex, published by Wearever--Proctor Silex Chillicothe, OH.

6 photographs of steam iron sole plates (2 sheets).

9 page collection of copies of advertisements Bosch,

Norelco, General Electric, Haz, Phillips, Braun(2) and Tefal(2).

Primary Examiner—Catherine E. Kemper
Attorney, Agent, or Firm—Dybvig & Dybvig

[57] CLAIM

The ornamental design for a steam iron, substantially as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a steam iron showing our new design, showing the top, front and left side thereof.

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view, the side opposite being a mirror image thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a fragmentary cross section taken substantially on line 7—7 of FIG. 6 and is representative of all of the holes and grooves in the sole plate of the iron shown in FIG. 6;

FIG. 8 is a fragmentary cross section taken substantially on line 8—8 of FIG. 6 and, except for the length of the groove, is representative of all of the holes with grooves extended therefrom in the sole plate of the steam iron as shown in FIG. 6.

FIG. 9 is a perspective view similar to FIG. 1, showing a modification thereof, the only difference being that there is only one button on top of the iron handle rather than the two buttons in the embodiment of FIGS. 1 through 8, the entire design of the embodiment of FIG. 9 being otherwise depicted in FIGS. 1 through 7; and

FIG. 10 is a perspective view similar to FIGS. 1 and 9, showing yet another embodiment thereof, the only difference in the embodiment of FIG. 10 and the embodiment of FIG. 9 being that there is no spray nozzle at the front of the iron of FIG. 10.




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-8




FIG-6




FIG-7



FIG-9




FIG-10

