

[54] SET OF HAND SIGNALS

[76] Inventor: Earl J. Breault, 4905 San Marque Cir., Carmichael, Calif. 95608

[**] Term: 14 Years

[21] Appl. No.: 810,269

[22] Filed: Dec. 17, 1985

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 500,560, Jun. 2, 1983, abandoned.

[52] U.S. Cl. D21/100; D20/33

[58] Field of Search 40/124.1, 418, 419, 40/421, 427, 445, 530, 586; D20/33; 446/26; 116/173-175; D21/100; D10/109

References Cited

U.S. PATENT DOCUMENTS

D. 260,626 9/1981 Kadar D11/160
D. 277,943 3/1985 Jones D20/33 X
528,256 10/1894 Morrison 40/586
2,687,006 8/1954 Lyons 40/421 X
2,781,462 2/1957 Wheeler et al. 40/421 X
3,484,974 12/1969 Culmone 40/586
3,969,837 7/1976 Kreese 40/586 X
4,352,461 10/1982 Orta et al. D20/33 X
4,455,963 6/1984 Matsuo D21/100 X
4,486,975 12/1984 Harreld et al. D21/100 X

FOREIGN PATENT DOCUMENTS

489076 5/1970 Switzerland 40/586


Primary Examiner—Catherine E. Kemper
Attorney, Agent, or Firm—Mark C. Jacobs

CLAIM

The ornamental design for set of hand signals, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a member of a set of hand signals, showing my new design;
FIG. 2 is a left side elevational view thereof;
FIG. 3 is a top plan view thereof;
FIG. 4 is a rear elevational view thereof;
FIG. 5 is a right side elevation view thereof;
FIG. 6 is a bottom plan view thereof;
FIG. 7 is a front elevational view of a second member of a set of hand signals;
FIG. 8 is a left side elevational view;
FIG. 9 is a top plan view thereof;
FIG. 10 is a rear elevational view thereof;
FIG. 11 is a right side elevational view thereof;
FIG. 12 is a bottom plan view thereof;
FIG. 13 is a front elevational view of a third member of a set of hand signals;
FIG. 14 is a left side elevational view thereof;
FIG. 15 is a top plan view thereof;
FIG. 16 is a rear elevational view thereof;
FIG. 17 is a right side elevational view thereof;
FIG. 18 is a bottom plan view thereof;
FIG. 19 is a front elevational view of a fourth member of a set of hand signals;
FIG. 20 is a left side elevational view thereof;
FIG. 21 is a rear elevational view thereof;
FIG. 22 is a right side elevational view thereof;
FIG. 23 is a top plan view thereof;
FIG. 24 is a top plan view of the second portion of the invention;
FIG. 25 is a bottom plan view thereof;
FIG. 26 is a rear elevational view of the support member, shown fully collapsed;
FIG. 27 is a top plan view thereof;
FIG. 28 is a front elevational view thereof;
FIG. 29 is a rear elevational view of the support shown fully extended;
FIG. 30 is a side elevational view of the support member and the fourth member of the set of hand signals, shown joined together;
FIG. 31 is a rear elevational view thereof;
FIG. 32 is an elevational view of the side opposite that shown in FIG. 30.






FIG. 1



FIG. 2



FIG. 3




FIG. 4




FIG. 6




FIG. 7



FIG. 8



FIG. 9




FIG. 10




FIG. 12




FIG. 13



FIG. 14



FIG. 15




FIG. 16





FIG. 18




FIG. 19



FIG. 20




FIG. 21



FIG. 22



FIG. 23



FIG. 25



FIG. 24




FIG. 26



FIG. 27




FIG. 28




FIG. 29



FIG. 30




FIG. 31



FIG. 32