

[54] **HAEMADYNAMOMETER**

[75] **Inventor: Koichi Tsukada, Shibukawa, Japan**

[73] **Assignee: Nihon Seimitsu Sokki Co., Ltd.,
Gunma, Japan**

[**] **Term: 14 Years**

[21] **Appl. No.: 789,225**

[22] **Filed: Oct. 18, 1985**

[52] **U.S. Cl. D24/21; D24/17**

[58] **Field of Search D24/17, 21; 128/651,
128/672-683, 686; D10/40, 46, 75, 81**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 254,806	4/1980	Kitai et al.	D24/17
D. 282,778	2/1986	Camens	D24/21
D. 288,478	2/1987	Carlson et al.	D24/17
D. 289,082	3/1987	Tsuji	D24/21
3,771,515	11/1973	Hurwitz	128/680

Primary Examiner—Wallace R. Burke
Assistant Examiner—Stella M. Reid
Attorney, Agent, or Firm—Armstrong, Nikaido,
Marmelstein & Kubovcik

[57] **CLAIM**

The ornamental design for a haemadynamometer, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a haemadynamometer showing my new design.

FIG. 2 is a bottom perspective view thereof.

FIG. 3 is a top plan view thereof.

FIG. 4 is a bottom plan view thereof.

FIG. 5 is a front elevational view thereof.

FIG. 6 is a back elevational view thereof.

FIG. 7 is a right side elevational view thereof.

FIG. 8 is a left side elevational view thereof.

The digital readout in FIG. 1 is shown for illustrative purposes only.




FIG. 1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8

