

United States Patent [19]

Yoshida et al.

[11] Patent Number: Des. 298,260

[45] Date of Patent: ** Oct. 25, 1988

[54] RANGE FINDING DEVICE FOR CLOSE-UP

[75] Inventors: Michio Yoshida, Tokyo; Isao Nakazawa, Kawasaki, both of Japan

[73] Assignee: Canon Kabushiki Kaisha, Tokyo, Japan

[**] Term: 14 Years

[21] Appl. No.: 813,956

[22] Filed: Dec. 27, 1985

[30] Foreign Application Priority Data

Jul. 8, 1985 [JP] Japan 60-29011

[52] U.S. Cl. D16/38; D16/10

[58] Field of Search D16/10, 32, 38, 44, D16/47; 354/80, 81, 162, 293; 355/39

[56] References Cited

U.S. PATENT DOCUMENTS

D. 197,257 12/1963 Fladlien D16/38

D. 257,259 10/1980 Shiraishi D16/44

2,466,171 4/1949 Hencke 355/39 X
3,687,030 8/1972 Dine 354/293
4,222,654 9/1980 Bodenhamer 354/293

Primary Examiner—Nelson C. Holtje
Attorney, Agent, or Firm—Fitzpatrick, Cella, Harper & Scinto

[57] CLAIM

The ornamental design for a range finding device for close-up, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a range finding device for close-up showing our new design;
FIG. 2 is a rear elevational view thereof;
FIG. 3 is a top plan view thereof;
FIG. 4 is a bottom plan view thereof;
FIG. 5 is a left side elevational view thereof;
FIG. 6 is a right side elevational view thereof;
FIG. 7 is a top and left front perspective view thereof;
FIG. 8 is a top and left front perspective view thereof wherein the rod is in a broken down and received position.




FIG. 1




FIG. 2



FIG. 3





FIG. 4







FIG. 7




FIG. 8

