

[54] CONTROL BUCKLE FOR POSITIONING AND RETAINING A DIVER'S WEIGHT

[76] Inventor: Steven L. Selisky, 2109 Gunflint Trail, Brooklyn Park, Minn. 55444

[**] Term: 14 Years

[21] Appl. No.: 255,427

[22] Filed: Oct. 11, 1988

[52] U.S. Cl. D3/100; D11/201; D11/237

[58] Field of Search D3/36, 106; D11/200, D11/201, 218, 236, 237

[56] References Cited

U.S. PATENT DOCUMENTS

D. 33,577	11/1900	Poalk	D11/218
D. 45,239	2/1914	Peterson	D11/218
D. 121,618	7/1940	Reiter	D11/218
D. 125,083	2/1941	Dickson	D11/218
D. 287,067	12/1986	Kasai	D11/218
D. 290,349	6/1987	Kasai	D11/218
1,913,413	6/1933	Schaefer	24/186
1,934,951	11/1933	Schaefer	24/186

2,084,412 6/1937 Schaefer 24/186


Primary Examiner—Bruce W. Dunkins
Assistant Examiner—Yvonne Brunot
Attorney, Agent, or Firm—James R. Cwayna

[57] CLAIM

The ornamental design for a control buckle for positioning and retaining a diver's weight, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view on a reduced scale of a control buckle for positioning and retaining a diver's weight showing my new design, a belt fragment and weight being shown therein in broken lines for illustrative purposes only;
FIG. 2 is a perspective view of the control buckle.
FIG. 3 is a top plan view thereof;
FIG. 4 is a side elevation thereof, the side opposite being identical thereto;
FIG. 5 is a bottom plan view thereof;
FIG. 6 is an end view thereof, the end opposite being identical thereto; and,
FIG. 7 is a vertical cross section taken substantially along line 7—7 of FIG. 3.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6



FIG. 7