[54] ADAPTOR FOR A GAME MACHINE CARTRIDGE

[75] Inventor: Yoshihiro Inoue, Kyoto, Japan

[73] Assignee: Nintendo Company Limited, Kyoto,

Japan

[**] Term: 14 Years

[21] Appl. No.: 2,000

[22] Filed: Jan. 9, 1987

[30] Foreign Application Priority Data

	TOTALE APPRICATION I HOTTLY DATA			
Oct	. 14, 1986 [JP]	Japan 61-40907		
[52]	U.S. Cl			
[58]	Field of Search			
	D14/116;	D3/35; D18/11, 12, 22; 206/312,		
	444; 27	3/148 B; 360/97, 98, 99, 132, 133;		
	361/392,	394, 395, 399, 415; 174/52.1, 52.4;		
•		369/291; D13/40, 41		

[56] References Cited

U.S. PATENT DOCUMENTS

D. 260,881	9/1981	McKinsey et al	
D. 292,399	10/1987	Yokawa	D14/114
2,952,810	9/1960	Helton	361/415 X
2,968,019	1/1961	Steinman et al	361/415 X
4,070,081	1/1978	Takahashi	361/399 X
4,114,044	9/1978	Chiulli .	
4,149,027	4/1979	Asher et al	
4,352,492	10/1982	Smith	361/399 X
4,480,835	11/1984	Williams .	
4,531,176	7/1985	Beecher, II .	
4,596,390	6/1986	Studley .	

FOREIGN PATENT DOCUMENTS

86306646 1/1985 European Pat. Off. .

2736823A1 3/1978 Fed. Rep. of Germany .

3313802A1 10/1983 Fed. Rep. of Germany .

2834 7/1979 Japan .

112352 3/1984 Japan .

52885 5/1985 Japan .

190372 9/1985 Japan .

2021334A 11/1979 United Kingdom .

OTHER PUBLICATIONS

Family Computer and Cartridge therefor, manufac-

tured by Nintendo Co., Ltd., Kyoto, Japan (Exhibits 1-6 attached).

Nintendo Entertainment Systems (NES), manufactured by Nintendo Co., Ltd., Kyoto, Japan and Nintendo of America, Inc. Redmond, Washington (Exhibits 1-6 attached).

Hong Kong Enterprise, "Floppy Disk Controller", Apr. 1984, p. 104.

U.S. patent application Ser. No. 900,818 filed Aug. 27, 1986.

U.S. patent application Ser. No. 801,240 filed May 27, 1977.

U.S. patent application Ser. No. 261,361 filed May 7, 1981.

Primary Examiner—Susan J. Lucas Assistant Examiner—Freda S. Nunn Attorney, Agent, or Firm—Nixon & Vanderhye

[57] CLAIM

The ornamental design for an adaptor for a game machine cartridge, as shown and described.

DESCRIPTION

FIG. 1 is a top, front and right side perspective view of an adaptor for a game machine cartridge showing my new design;

FIG. 2 is a bottom, rear and right side perspective view thereof;

FIG. 3 is a top plan view thereof;

FIG. 4 is a bottom plan view thereof;

FIG. 5 is a right side elevational view thereof, the left side being a mirror image;

FIG. 6 is a rear elevational view thereof;

FIG. 7 is a front elevational view thereof;

FIG. 8 is a front, top and right side perspective view of a second embodiment of my new design;


FIG. 9 is a top plan view thereof, the remaining undisclosed views of the second embodiment are similar to those shown in FIGS. 4-7 of the first embodiment;

FIG. 10 is a top, front, right side perspective view of a third embodiment of my new design;

FIG. 11 is a bottom, rear, right side perspective view thereof;

FIG. 12 is a top plan view thereof;

FIG. 13 is a bottom plan view thereof;



•

FIG. 14 is a right side elevational view thereof, the left side being a mirror image;


FIG. 15 is a rear elevational view thereof;

·

FIG. 16 is a front elevational view thereof;

FIG. 17 is a top, front, right side perspective view of a fourth embodiment of my new design;

FIG. 18 is a top, plan view thereof, the remaining undisclosed views are the same as FIGS. 11-16 of the third embodiment.






FIG. 3




FIG.4




FIG.5




FIG. 6




FIG. 7





FIG. 8



•

FIG.9






FIG. 10








FIG. 12




FIG. 18




FIG. 13

.

•

•




FIG. 14




FIG. 15



FIG. 16

