

[54] CONTROL CONSOLE SET FOR  
TELEPHONE EXCHANGES

[75] Inventors: **Franco Raggi**; **Alberto Meda**, both of Milan; **Denys Santachiara**, Campagnola Emilia; **Piercarlo Ravasio**, Arlate di Calco; **Antonio Martusciello**, S. Nicola, all of Italy

[73] Assignee: **Italtel Telematica s.p.a.**, Capua Vetere, Italy

[\*\*] Term: **14 Years**

[21] Appl. No.: **326,249**

[22] Filed: **Mar. 21, 1989**

[30] Foreign Application Priority Data

Sep. 28, 1988 [IT] Italy ..... 21929/88[U]  
[52] U.S. Cl. .... **D14/241; D14/149**  
[58] Field of Search ..... **D14/241, 242, 151, 148;**  
379/267, 262, 263, 218, 164, 419, 420, 441, 440,  
433, 436

[56] References Cited

U.S. PATENT DOCUMENTS

D. 254,436 3/1980 Bakal ..... D14/241  
D. 273,954 5/1984 Bee ..... D14/241  
D. 298,126 10/1988 Weisz et al. .... D14/151 X  
D. 298,937 12/1988 Dunstall et al. .... D14/151  
D. 300,029 2/1989 Kido et al. .... D14/241  
D. 300,320 3/1989 Watanabe et al. .... D14/241  
4,097,691 6/1978 Ehrlich et al. .... D14/242 X  
4,385,212 5/1983 Tyler ..... 379/440  
4,773,090 9/1988 Gaatman ..... D14/151 X  
4,782,514 11/1988 Oshikata et al. .... 379/165  
4,817,132 3/1989 Chamberlin ..... 379/164 X

FOREIGN PATENT DOCUMENTS

0296438 12/1988 Japan ..... 379/419

OTHER PUBLICATIONS

Commutation of Transmission (France), Dec. 1984; at p. 6—"C/Set" Attendant Position for Diapason Exchange.

Primary Examiner—Horace B. Fay, Jr.  
Attorney, Agent, or Firm—Birch, Stewart, Kolasch & Birch

[57] CLAIM

The ornamental design for a control console set for telephone exchanges, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a control console set for telephone exchanges showing our new design with the handset and stand in cradled relationship and attached to the side of the console, and with the display panel of the console in raised operative position; FIG. 2 is a left side perspective view thereof; FIG. 3 is a right side perspective view thereof; FIG. 4 is a rear and right side perspective view thereof with the display panel seated in flush relationship with the console surface; FIG. 5 is a left side and front perspective view of a second embodiment thereof, with the handset and stand in cradled relationship and attached to the left side of the console; FIG. 6 is a front perspective view of the first embodiment with the display panel seated in flush surface relationship with the console surface, and with a left side, bottom perspective view of the handset attached to the console and spaced apart from the stand, and a left side, perspective view of the stand alone; and FIG. 7 is a right side perspective view of the first embodiment with the display panel in raised operative position and with a right side and top perspective view of the stand, and a bottom, left side perspective view of the handset alone which is attached to the console. The sole difference of the embodiments is attachment of the handset by an extension plug to the rear protruding receptacle member of the console shown in FIG. 4.





FIG. 1








FIG. 2

FIG. 3






FIG. 4




FIG. 5



FIG. 6

