

[54] GAUGE INDICATOR

[76] Inventor: Vincent D. Reilly, 219 Engle St., Tenafly, N.J. 07670

[**] Term: 14 Years

[21] Appl. No.: 104,496

[22] Filed: Oct. 5, 1987

[52] U.S. Cl. D10/103

[58] Field of Search D10/46, 61, 63, 65, D10/70, 74, 102, 103, 122, 127; 33/300, 303, 349; 116/327, 328, 332

[56] References Cited

U.S. PATENT DOCUMENTS

D. 85,727	12/1931	Teague	D10/46
D. 93,855	11/1934	Suhr	D10/46
D. 94,285	1/1935	Side et al.	D10/46
D. 190,097	4/1961	Erbguth	D10/46
D. 233,552	11/1974	Schwartz	D10/98
438,541	10/1890	Green	33/349

2,920,603	1/1960	Burger	116/328 X
3,142,148	7/1964	Morgan et al.	116/332 X

FOREIGN PATENT DOCUMENTS

103248	2/1924	Switzerland	116/332
141357	10/1930	Switzerland	116/327
914194	12/1962	United Kingdom	116/332

Primary Examiner—Nelson C. Holtje
Assistant Examiner—Antoine D. Davis

[57] CLAIM

The ornamental design for gauge indicator, as shown.

DESCRIPTION

FIG. 1 is a top, front, and left side perspective view of a gauge indicator showing my new design; FIG. 2 is a front elevational view; FIG. 3 is a rear elevational view; FIG. 4 is a top plan view; FIG. 5 is a left side elevational view, the right side elevational view being a mirror image; and FIG. 6 is a bottom plan view thereof.



