

[54] **LOCKING BRACKET FOR HOLDING TIE ROD ENDS EMPLOYED WITH CONCRETE FORMWORK**

[75] **Inventor: H. Gordon Gates, Lakewood, Colo.**

[73] **Assignee: Gates & Sons, Inc., Denver, Colo.**

[**] **Term: 14 Years**

[21] **Appl. No.: 222,717**

[22] **Filed: Jul. 18, 1988**

[52] **U.S. Cl. D8/336**

[58] **Field of Search D8/330-331, D8/336, 338; 292/DIG. 9, DIG. 27, DIG. 53, 44, 48, 57, 80, 240, 300, 304, 305, 143; 70/57, 58, 61-62**

[56] **References Cited**

U.S. PATENT DOCUMENTS

- D. 33,618 11/1900 Taylor D8/337
- D. 34,280 3/1901 Monroe D8/337
- D. 50,376 2/1917 Ehrlich D8/338

D. 273,932 5/1984 Gates D8/330

Primary Examiner—Wallace R. Burke

Assistant Examiner—Brian N. Vinson


Attorney, Agent, or Firm—Fields, Lewis, Pittenger & Rost


[57] **CLAIM**

The ornamental design for the locking bracket for holding tie rod ends employed with concrete formwork, as shown and described.


DESCRIPTION

FIG. 1 is a top, front, and left side perspective view of a locking bracket for holding tie rod ends employed with concrete formwork showing my new design; FIG. 2 is a front elevational view thereof; FIG. 3 is a right side elevational view thereof; FIG. 4 is a rear elevational view thereof; FIG. 5 is a left side elevational view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; and FIG. 8 is a top, rear, and right side perspective view thereof.







Fig_1




Fig_2




Fig_3




Fig_4




Fig_5



Fig_6



Fig_7



Fig_8