

[54] FLASHING EMERGENCY SIGNAL FOR VEHICLES

[76] Inventor: Yoshio Kondo, Room No. 311, Eruarukasaru Nishinipori, No. 29-11, Nishinipori 6-chome, Arakawa-ku, Tokyo, Japan

[**] Term: 14 Years

[21] Appl. No.: 194,287

[22] Filed: May 16, 1988

Related U.S. Application Data

[63] Continuation of Ser. No. 1,430, Jan. 8, 1987, abandoned.

[30] Foreign Application Priority Data

Jul. 31, 1986 [JP] Japan 61-29806

Aug. 5, 1986 [JP] Japan 61-119388

[52] U.S. Cl. D10/114; D10/109

[58] Field of Search D26/28-36; D10/114, 113, 109, 111; 362/61; 340/468, 471-479; 40/591, 592; 116/28 R

[56] References Cited

U.S. PATENT DOCUMENTS

D. 228,527	10/1973	Arnce et al.	D10/114
4,157,531	6/1979	Mont	362/362 X
4,613,847	9/1986	Scolari et al.	340/473
4,875,028	10/1979	Chou	340/473

Primary Examiner—Susan J. Lucas
Attorney, Agent, or Firm—Wenderoth, Lind & Ponack

[57] CLAIM

The ornamental design for a flashing emergency signal for vehicles, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a flashing emergency signal for vehicles showing my new design; FIG. 2 is a front elevational view thereof; FIG. 3 is a rear elevational view thereof; FIG. 4 is a side elevational view thereof, the opposite side being a mirror image; FIG. 5 is a top plan view thereof; FIG. 6 is a bottom plan view thereof. The two triangular portions of the front surface are shaded with oblique lines to indicate translucency.




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.

