United States Patent [19]

Adam

[11] Patent Number: Des. 314,363 [45] Date of Patent: ** Feb. 5, 1991

[54]	TIRE TREAD		
[75]	Inventor:	Georges Adam, Bissen, Luxembourg	
[73]	Assignee:	The Goodyear Tire & Rubber Company, Akron, Ohio	
[*]	Notice:	The portion of the term of this patent subsequent to Nov. 6, 2004 has been disclaimed.	
[**]	Term:	14 Years	
[21]	Appl. No.:	211,527	
[22] [52] [58]	Filed: Jun. 20, 1988 U.S. Cl		
[56]	References Cited		
	U.S. PATENT DOCUMENTS		

FOREIGN PATENT DOCUMENTS

8502311.6 2/1985 Fed. Rep. of Germany. 642882 3/1985 Japan.

2018208	7/1979	United Kingdom .
D955804	3/1980	United Kingdom .
1006180	2/1982	United Kingdom .
1024079	11/1985	United Kingdom.

OTHER PUBLICATIONS

1987 Tread Design Guide, p. 152, Toyo M-54 Tire, second row down from top, left side of page.

1987 Tread Design Guide, p. 155, Yokohama Super Steel Y798R Tire, third row down from top, second tire in from left side of page.

1987 Tread Design Guide, p. 198, Sumitomo ST727 Tire, second row down from top, second tire in from left side of page.

Primary Examiner—James M. Gandy Attorney, Agent, or Firm—L. R. Drayer

[57] CLAIM

The ornamental design for a tire tread, as shown and described.


DESCRIPTION

FIG. 1 is a top plan view of a tire tread showing my new design which has been broken away in the middle to indicate indeterminate length it being understood that the tread pattern is repeated uniformly throughout its length;


FIG. 2 is a greatly enlarged fragmentary top plan view thereof;

FIG. 3 is a cross sectional view taken along line 3—3 in FIG. 2; and


FIG. 4 is an enlarged perspective view thereof formed into a ring as it would appear attached to a tire carcass.



Feb. 5, 1991







F1G.2

Feb. 5, 1991




FIG.4