

[54] ELECTRICAL CURRENT INDICATING DEVICE

[76] Inventor: James E. Bubash, 252 Sunset Dr., Ballwin, Mo. 63011

[**] Term: 14 Years

[21] Appl. No.: 113,808

[22] Filed: Oct. 26, 1987

[52] U.S. Cl. D10/78; D10/75

[58] Field of Search D10/75, 78, 103; 324/95, 117 R, 126, 127, 129; 340/644, 664

[56] References Cited

U.S. PATENT DOCUMENTS

3,324,393	6/1967	Casey et al.	324/127
3,684,955	8/1972	Adams	324/127 X
3,771,049	11/1973	Piccione	324/127 X
4,309,655	1/1982	Lienhard et al.	324/127 X
4,513,274	4/1985	Halder	324/127 X
4,525,669	6/1985	Holberton et al.	324/127 X
4,611,207	9/1986	Anderson et al.	324/126 X
4,728,887	3/1988	Davis	324/127
4,758,962	7/1988	Fernandes	324/127
4,796,027	1/1989	Smith-Vaniz	324/127 X
4,804,917	2/1989	Miller et al.	324/126 X
4,841,237	6/1989	Landre	324/127
4,901,010	2/1990	Bernard	324/117 R X

Primary Examiner—Nelson C. Holtje

Assistant Examiner—Antoine D. Davis

Attorney, Agent, or Firm—Senniger, Powers, Leavitt & Roedel

[57] CLAIM

The ornamental design for electrical current indicating device, as shown and described.

DESCRIPTION

FIG. 1 is a top, front, and right side perspective view showing one embodiment of a design for a current indicating device;

FIG. 2 is a front elevational view of the current indicating device of FIG. 1, the rear elevational view being identical;

FIG. 3 is a left side elevational view of the current indicating device of FIG. 1;

FIG. 4 is a top plan view of the current indicating device of FIG. 1;

FIG. 5 is a bottom plan view of the current indicating device of FIG. 1;

FIG. 6 is a top, front, and right side perspective view showing a second embodiment of a design for a current indicating device;

FIG. 7 is a front elevational view of the current indicating device of FIG. 6, the rear elevational view being identical;

FIG. 8 is a left side elevational view of the current indicating device of FIG. 6;

FIG. 9 is a top plan view of the current indicating device of FIG. 6;

FIG. 10 is a bottom plan view of the current indicating device of FIG. 6;

FIG. 11 is a top, front, and right side perspective view showing a third embodiment of a design for a current indicating device;

FIG. 12 is a front elevational view of the current indicating device of FIG. 11, the rear elevational view being identical;

FIG. 13 is a left side elevational view of the current indicating device of FIG. 11;

FIG. 14 is a top plan view of the current indicating device of FIG. 11;

FIG. 15 is a bottom plan view of the current indicating device of FIG. 11;

FIG. 16 is a top, front, and right side perspective view showing a fourth embodiment of a design for a current indicating device;

FIG. 17 is a front elevational view of the current indicating device of FIG. 16, the rear elevational view being identical;

FIG. 18 is a left side elevational view of the current indicating device of FIG. 16;

FIG. 19 is a top plan view of the current indicating device of FIG. 16;

FIG. 20 is a bottom plan view of the current indicating device of FIG. 16;

FIG. 21 is a top, front, and right side perspective view showing a fifth embodiment of a design for a current indicating device;

FIG. 22 is a front elevational view of the current indicating device of FIG. 21, the rear elevational view being identical;




FIG. 23 is a left side elevational view of the current indicating device of FIG. 21;

FIG. 24 is a top plan view of the current indicating device of FIG. 21;

FIG. 25 is a bottom plan view of the current indicating device of FIG. 21;

FIG. 26 is a top, front, and right side perspective view showing a sixth embodiment of a design for a current indicating device;

FIG. 27 is a front elevational view of the current indicating device of FIG. 26, the rear elevational view being identical;

FIG. 28 is a left side elevational view of the current indicating device of FIG. 26;

FIG. 29 is a top plan view of the current indicating device of FIG. 26;

FIG. 30 is a bottom plan view of the current indicating device of FIG. 26;

FIG. 31 is a top, front, and right side perspective view showing a seventh embodiment of a design for a current indicating device;

FIG. 32 is a front elevational view of the current indicating device of FIG. 31, the rear elevational view being identical;

FIG. 33 is a left side elevational view of the current indicating device of FIG. 31;

FIG. 34 is a top plan view of the current indicating device of FIG. 31; and

FIG. 35 is a bottom plan view of the current indicating device of FIG. 31.

FIG. 1.




FIG. 2.




FIG. 3.



FIG. 4.



FIG. 5.



FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.



FIG. 10.




FIG. 11.




FIG. 12.




FIG. 13.




FIG. 14.



FIG. 15.



FIG. 16.




FIG. 17.




FIG. 18.




FIG. 19.



FIG. 20.



FIG. 21.




FIG. 22.




FIG. 23.



FIG. 24.




FIG. 25.



FIG. 26.




FIG. 27.




FIG. 28.




FIG. 29.



FIG. 30.




FIG. 31.




FIG. 32.




FIG. 33.




FIG. 34.




FIG. 35.

