

[54] **FLOATABLE SIGNAL LIGHT**

[75] **Inventor: Harold S. Sinrod, Potomac, Md.**

[73] **Assignee: Loud-Stik Corporation, Rockville, Md.**

[**] **Term: 14 Years**

[21] **Appl. No.: 150,313**

[22] **Filed: Jan. 26, 1988**

[52] **U.S. Cl. D10/114; D10/107; D26/40**

[58] **Field of Search D10/114, 109, 107, 111; D12/316; 441/1, 6, 11-13; 116/107; 340/984, 985, 388, 405**

[56] **References Cited**

U.S. PATENT DOCUMENTS

366,077	7/1887	Delany	441/1
849,362	4/1907	Beebe	441/6
1,709,890	4/1929	Wilckens	116/107
2,765,481	10/1956	Manhart et al.	D26/40 X
3,138,795	6/1964	Wallace et al.	116/107 X
3,280,789	10/1966	Lewis et al.	441/11 X
3,407,417	10/1968	Garland	441/1
4,077,076	3/1978	Masters	116/107 X
4,781,636	11/1988	Schurr	441/6

FOREIGN PATENT DOCUMENTS

0230888 12/1984 Japan 441/13

Primary Examiner—Susan J. Lucas
Attorney, Agent, or Firm—Samuel Meerkreebs

[57] **CLAIM**

The oramental design for floatable signal light, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a floatable signal light showing my new design;
 FIG. 2 is an elevational view of FIG. 1;
 FIG. 3 is an elevational view taken at 90° to FIG. 2;
 FIG. 4 is a bottom plan view of FIG. 2;
 FIG. 5 is a top plan view of FIG. 2;
 FIG. 6 is a perspective view, similar to FIG. 1, showing an upper modified portion;
 FIG. 7 is an elevational view, similar to FIG. 2, showing the upper portion of FIG. 6;
 FIG. 8 is a perspective view, similar to FIG. 1 showing a modified, intermediate float;
 FIG. 9 is a perspective view, similar to FIG. 1, showing still another modified intermediate float;
 FIG. 10 is a perspective view, similar to FIG. 1, showing yet another modified intermediate float; and
 FIG. 11 is a perspective view, similar to FIG. 1, showing a still further modified intermediate float.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

