

[54] **ERGONOMIC CUSHION**

[76] Inventor: **Nathan Edelson**, 526 Hickory St., Missoula, Mont. 59801

[**] Term: **14 Years**

[21] Appl. No.: **447,708**

[22] Filed: **Dec. 8, 1989**

[52] U.S. Cl. **D6/601; D6/596**

[58] Field of Search **D6/595-596, D6/601, 605, 382, 383; 5/417, 419-420, 431-433, 434, 436-437, 443, 446, 448, 465**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 229,639	12/1973	Woog	D6/596
D. 246,816	1/1978	Tam et al.	D6/596
D. 279,531	7/1985	Rogers, Jr.	D6/601
D. 295,248	4/1988	Sommerfield et al.	D6/601
D. 309,393	7/1990	Talanjon	D6/601
3,648,308	3/1972	Greenawalt	5/431 X
4,193,150	3/1980	Vineberg	5/431

Primary Examiner—Wallace R. Burke

Assistant Examiner—Brian N. Vinson

[57] **CLAIM**

The ornamental design for an ergonomic cushion, as shown and described.

DESCRIPTION

FIG. 1 is a top, side, and end perspective view of an

ergonomic cushion showing my new design, the opposite side being a mirror image of that shown;

FIG. 2 is a top, side, and end perspective view thereof, with the head pad portion shown in an alternative position;

FIG. 3 is a top, side, and end elevational view thereof shown partially folded;

FIG. 4 is a top and end perspective view thereof, with the head pad portion shown in an alternative position;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a top, side, and end perspective view of a second embodiment thereof, the opposite side being a mirror image of that shown;




FIG. 7 is a top, end, and side perspective view of a third embodiment thereof, the opposite side being a mirror image of that shown, and the bottom being plain and unornamented;

FIG. 8 is a top, end, and side perspective view of the embodiment of FIG. 7, with the elbow rest pads shown secured in an alternative position;

FIG. 9 is a top, side, and end perspective view of a fourth embodiment thereof, the opposite side being a mirror image of that shown, and the bottom being plain and unornamented;

FIG. 10 is a top, side, and end elevational view of a fifth embodiment thereof, the opposite side being a mirror image of that shown, and the bottom being plain and unornamented; and

FIG. 11 is a top, side, and end elevational view of the embodiment of FIG. 10, with the elbow rest pads being shown secured in an alternative position.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

Fig. 8





Fig. 9




Fig. 10




Fig. 11