

[54] BATTERY CHARGER

[75] Inventors: Kuniyki Shimoo, Sumoto; Kazuo Takada, Nara, both of Japan

[73] Assignee: Sanyo Electric Co., Ltd., Osaka, Japan

[**] Term: 14 Years

[21] Appl. No.: 361,920

[22] Filed: Jun. 6, 1989

[30] Foreign Application Priority Data

Dec. 6, 1988 [JP] Japan 63-47532

[52] U.S. Cl. D13/107

[58] Field of Search D13/107, 108, 109, 120, D13/184; D14/253, 100, 101, 107; 320/2, 3, 4, 5

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 241,555 9/1976 Goldman et al. D13/107
- D. 278,703 5/1985 Chiodo et al. D13/107
- D. 278,704 5/1985 Claxton et al. D13/107
- D. 298,136 10/1988 Toth et al. D13/107 X

FOREIGN PATENT DOCUMENTS

0708888 4/1987 Japan .

OTHER PUBLICATIONS

Battery Chargers, on p. 112 of *Radio Shack Catalog*, No. 406, 1987.

Battery Charger, on p. 131 of *Hardware Age*, 3-88.

Primary Examiner—Susan J. Lucas
Assistant Examiner—J. Sincavage
Attorney, Agent, or Firm—Darby & Darby

[57] CLAIM

The ornamental design for a battery charger, as shown and described.

DESCRIPTION

FIG. 1 is a front, top and right side perspective view of a battery charger showing my new design;

FIG. 2 is a front, top and right side perspective view thereof with the lid in the open position. The broken line showing of the battery module is included for the purpose of illustrating environmental elements only and forms no part of the claimed design.

FIG. 3 is a top plan view thereof;

FIG. 4 is a top plan view thereof with the lid in the open position;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is an inverted rear elevational view thereof;

FIG. 7 is a front elevational view thereof;

FIG. 8 is a right side elevational view thereof;

FIG. 9 is a left side elevational view thereof.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8




FIG. 9

