

[54] COMBINED REVERSIBLE SPRINKLER NOZZLE AND SUPPORT RING

[76] Inventor: Robert W. Hengesbach, 7886 Munson Rd., Mentor, Ohio 44060

[**] Term: 14 Years

[21] Appl. No.: 414,068

[22] Filed: Sep. 28, 1989

Related U.S. Application Data

[60] Division of Ser. No. 224,249, Jul. 26, 1988, which is a continuation of Ser. No. 20,684, Mar. 2, 1987, which is a continuation-in-part of Ser. No. 674,272, Nov. 23, 1984, which is a continuation-in-part of Ser. No. 461,874, Jan. 28, 1983, Pat. No. Des. 282,392.

[52] U.S. Cl. D23/213

[58] Field of Search D23/213-230; 239/396

[56] References Cited

U.S. PATENT DOCUMENTS

Table of references cited including patent numbers, dates, names, and classification codes.

Table of references cited including patent numbers, dates, names, and classification codes.

OTHER PUBLICATIONS

Brochure, Tri-Con., Inc., 4 pages, dated 1/1/1977, entitled: We Make The System. Brochure, Spraying Systems Co., Catalog 27, pp. 75-79, 1978, entitled: Spray Nozzles and Accessories. Brochure, Tri-Con., Inc., 4 pages, date unknown, entitled: The Tri-Con All Purpose Nozzle. Trademark Reg. No. 1,352,262 Registered Jul. 30, 1985. Trademark Reg. Nos. 1,379,809, 1,379,810, 1,379,811 Registered Jan. 21, 1986.


Primary Examiner—James R. Largen Attorney, Agent, or Firm—David A. Burge

[57] CLAIM

The ornamental design for a combined reversible sprinkler nozzle and support ring, as shown and described.

DESCRIPTION

FIG. 1 is a bottom perspective view of a combined reversible sprinkler nozzle and support ring showing my new design; FIG. 2 is a top plan view thereof; FIG. 3 is a bottom perspective view of a second embodiment thereof; FIG. 4 is a top plan view of FIG. 3; FIG. 5 is a bottom perspective view of a third embodiment thereof; FIG. 6 is a bottom perspective view of a fourth embodiment thereof; FIG. 7 is a bottom perspective view of a fifth embodiment thereof; FIG. 8 is a bottom perspective view of a sixth embodiment thereof; FIG. 9 is a bottom perspective view of a seventh embodiment thereof; and FIG. 10 is a bottom perspective view of an eighth embodiment thereof.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10