



US00D326503S

# United States Patent [19]

[11] Patent Number: Des. 326,503

Ipsen

[45] Date of Patent: \*\* May 26, 1992

[54] VALVE FOR A TRANSPORTABLE CONTAINER SUCH AS A KEG FOR DISTRIBUTING A DRINKABLE LIQUID SUCH AS BEER, WINE OR CIDER UNDER PRESSURE OF A GAS SUCH AS CO<sub>2</sub>

[75] Inventor: Bernt Ipsen, Morud, Denmark  
[73] Assignee: Micro Matic A/S, Odense, Denmark  
[\*\*] Term: 14 Years  
[21] Appl. No.: 448,586  
[22] Filed: Dec. 11, 1989

[30] Foreign Application Priority Data  
Jun. 19, 1989 [DK] Denmark ..... MA 0739 1989  
[52] U.S. Cl. .... D23/233  
[58] Field of Search ..... D23/233-237;  
137/209, 212; 222/400.7, 464; D7/300, 397, 398

[56] References Cited  
U.S. PATENT DOCUMENTS  
4,351,456 9/1982 Nezworski ..... 137/212  
4,406,301 9/1983 Cerrato ..... 137/212  
4,458,833 7/1984 Bailey ..... 222/400.7  
4,685,598 8/1987 Nezworski ..... 222/400.7


FOREIGN PATENT DOCUMENTS  
2170488 8/1986 United Kingdom ..... 222/464  
*Primary Examiner*—James M. Gandy  
*Assistant Examiner*—Lisa Lichtenstein  
*Attorney, Agent, or Firm*—Oliff & Berridge

[57] CLAIM  
The ornamental design for a valve for a transportable container such as a keg for distributing a drinkable

liquid such as beer, wine or cider under pressure of a gas such as CO<sub>2</sub>, as shown and described.

### DESCRIPTION

FIG. 1 is a top and side perspective view of a valve for a transportable container such as a keg for distributing a drinkable liquid such as beer, wine, or cider under pressure of a gas such as CO<sub>2</sub>, showing my new design, the opposite side being a mirror image of that shown; FIG. 2 is a bottom and side perspective view thereof; FIG. 3 is a side elevational view thereof; FIG. 4 is a top plan view thereof; FIG. 5 is a bottom plan view thereof; FIG. 6 is a bottom and side perspective view of a siphon tube shown separately for clarity of illustration, the opposite side being a mirror of that shown; FIG. 7 is a top and side perspective view of FIG. 6; FIG. 8 is a side elevational view of FIG. 6; FIG. 9 is a top plan view of FIG. 8; FIG. 10 is a bottom plan view of FIG. 8; FIG. 11 is a top and side perspective view of a collar, shown separately for clarity of illustration, the opposite side being a mirror image of that shown; FIG. 12 is a bottom and side perspective view of FIG. 11; FIG. 13 is a side elevational view of FIG. 11; FIG. 14 is a top plan view of FIG. 11; FIG. 15 is a bottom plan view of FIG. 11; FIG. 16 is a top and side perspective view of a housing of the claimed design, shown separately for clarity of illustration; FIG. 17 is a bottom and side perspective view of FIG. 16; FIG. 18 is a side elevational view of FIG. 16; FIG. 19 is a top plan view of FIG. 16; and, FIG. 20 is a bottom plan view of FIG. 16.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20