



US00D327657S

United States Patent [19]

[11] Patent Number: **Des. 327,657**

Marcou et al.

[45] Date of Patent: **** Jul. 7, 1992**

[54] **INFRARED SIGNAL DETECTOR**

3,619,629	11/1971	Matthews	340/556
4,012,731	3/1977	Solomon	340/341
4,037,223	7/1977	Tucci et al.	340/571
4,191,947	3/1980	Bouchard et al.	340/541

[75] Inventors: **Jean-Claude Marcou, Fayetteville; Edward B. Hubben, Skaneateles, both of N.Y.**

[73] Assignee: **Pass & Seymour, Inc., Syracuse, N.Y.**

[**] Term: **14 Years**

[21] Appl. No.: **532,981**

[22] Filed: **Jun. 4, 1990**

[52] U.S. Cl. **D10/106**

[58] Field of Search **D10/104, 105, 106, 121; D8/404; D13/137, 138, 139; 340/541, 571, 556, 546, 572**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 275,462	9/1984	Beeson et al.	D10/106
D. 275,464	9/1984	Beeson et al.	D10/106
D. 307,560	5/1990	Andrews et al.	D10/106
3,390,388	6/1968	Kahl, Jr. et al.	340/556


Primary Examiner—James M. Gandy
Assistant Examiner—Marcus Jackson
Attorney, Agent, or Firm—Charles S. McGuire

[57] **CLAIM**

The ornamental design for infrared signal detector, as shown and described.

DESCRIPTION

FIG. 1 is a reduced front perspective view of an infrared signal detector showing our new design; FIG. 2 is a front elevational view thereof; FIG. 3 is a right side elevational view thereof, with left side being a mirror image, and with the wires broken away to indicate indeterminate length; FIG. 4 is a rear elevational view thereof; FIG. 5 is a top plan view thereof; and, FIG. 6 is a bottom plan view thereof.






FIG. 1




FIG. 5




FIG. 6




FIG. 2




FIG. 3




FIG. 4