



US00D328352S

United States Patent [19]

[11] Patent Number: Des. 328,352

Futatsuka

[45] Date of Patent: ** Jul. 28, 1992

[54] COMBINATION TEMPERATURE AND HUMIDITY CHAMBER

DESCRIPTION

[75] Inventor: Mitsuyoshi Futatsuka, Nishinomiya, Japan

FIG. 1 is a perspective view of a combination temperature and humidity chamber showing my new design;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a rear elevational view thereof;

FIG. 4 is a left side elevational view thereof;

FIG. 5 is a right side elevational view thereof;

FIG. 6 is a top plan view thereof;

FIG. 7 is a bottom plan view thereof;

FIG. 8 is a perspective view of an alternate embodiment of the design shown in FIG. 1;

FIG. 9 is a front elevational view of FIG. 8;

FIG. 10 is a rear elevational view of FIG. 8;

FIG. 11 is a left side elevational view of FIG. 8;

FIG. 12 is a right side elevational view of FIG. 8;

FIG. 13 is a top plan view of FIG. 8;

FIG. 14 is a bottom plan view of FIG. 8;

FIG. 15 is a perspective view of a second embodiment of the design shown in FIG. 1;

FIG. 16 is a front elevational view of FIG. 15;

FIG. 17 is a rear elevational view of FIG. 15;

FIG. 18 is a left side elevational view of FIG. 15;

FIG. 19 is a right side elevational view of FIG. 15;

FIG. 20 is a top plan view of FIG. 15;

FIG. 21 is a bottom plan view of FIG. 15;

FIG. 22 is a perspective view of a third embodiment of the design shown in FIG. 1;

FIG. 23 is a front elevational view of FIG. 22;

FIG. 24 is a rear elevational view of FIG. 22;

FIG. 25 is a left side elevational view of FIG. 22;

FIG. 26 is a right side elevational view of FIG. 22;

FIG. 27 is a top plan view of FIG. 22; and,

FIG. 28 is a bottom plan view of FIG. 22.

[**] Term: 14 Years

[21] Appl. No.: 429,902

[22] Filed: Oct. 30, 1989

[52] U.S. Cl. D24/232

[58] Field of Search D24/113, 128, 130, 133, D24/140, 143, 146, 147, 150, 187, 189, 199, 200, 216, 219, 224, 227, 229, 232; 73/300; 128/419 P, 660.1, 660.5, 662.03, 749, 752, 758, 784, 785; 312/236; 604/107, 111, 119, 187, 192, 210, 232, 263, 403, 407; 606/107, 119, 128, 130, 157, 158, 176, 205-207

[56] References Cited

U.S. PATENT DOCUMENTS

D. 297,361	8/1988	Yamamoto et al.	D24/232
D. 297,564	9/1988	Yamamoto et al.	D24/232
3,160,452	12/1964	Rothman	312/236
4,704,870	11/1987	Beitner	312/236

Primary Examiner—A. Hugo Word

Assistant Examiner—Celia A. Murphy

Attorney, Agent, or Firm—Jordan and Hamburg

[57] CLAIM

The ornamental design for a combination temperature and humidity chamber, as shown and described.




FIG.1




FIG. 2




FIG. 3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG.10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG.15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21.




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28

