



US00D328714S

United States Patent [19]

[11] Patent Number: **Des. 328,714**

Nakajima et al.

[45] Date of Patent: **** Aug. 18, 1992**

[54] ULTRASONIC FLAW DETECTOR

[76] Inventors: **Hiroaki Nakajima**, 16-4, 6-chome, Setagaya-ku, Tokyo; **Kazuhiko Hiraoka**, 16-10, Tateno-cho, Nerima-ku, Tokyo; **Yukio Arima**, 4-24, Inarimae, Tsukuba-shi, Ibaragi-ken; **Hiroaki Yanagimoto**; **Tetsuyoshi Tominaga**, both of 1828, Ohaza Niihari, Chiyoda-mura, Niihari-gun, Ibaragi-ken, all of Japan

[**] Term: **14 Years**

[21] Appl. No.: **558,190**

[22] Filed: **Jul. 26, 1990**

[30] Foreign Application Priority Data

Apr. 27, 1990 [JP] Japan 1-14282
 [52] U.S. Cl. **D10/75; D10/46**
 [58] Field of Search **D10/46, 75; 73/606, 73/607, 621, 629, 618, 649, 658, 659, 660**

[56] References Cited

U.S. PATENT DOCUMENTS

D. 219,306	11/1970	Morgan	D10/46
D. 275,277	8/1984	Barbo et al.	D10/46 X
D. 307,398	4/1990	Umemoto et al.	D10/46
2,378,237	6/1945	Morris	73/618 X
3,780,572	12/1973	Rocha	73/607

Primary Examiner—Donald P. Walsh
Assistant Examiner—Antoine D. Davis
Attorney, Agent, or Firm—Antonelli, Terry, Stout & Kraus

[57] CLAIM

The ornamental design for an ultrasonic flaw detector, as shown.

DESCRIPTION

FIG. 1 is a perspective view of an ultrasonic flaw detector showing our new design;
 FIG. 2 is a front elevational view;
 FIG. 3 is a top plan view;
 FIG. 4 is a left side elevational view;
 FIG. 5 is a right side elevational view;
 FIG. 6 is a rear elevational view;
 FIG. 7 is a bottom plan view; and,
 FIG. 8 is a perspective view thereof, shown with the tray element in an extended condition.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

