



US00D329444S

United States Patent [19]

[11] Patent Number: Des. 329,444

Rauch

[45] Date of Patent: ** Sep. 15, 1992

[54] **COMBINED VISOR AND EYE SHIELD**

[76] Inventor: **Robert A. Rauch**, 21621 Fernleaf, El Toro, Calif. 92630

[**] Term: **14 Years**

[21] Appl. No.: **579,140**

[22] Filed: **Sep. 11, 1990**

4,821,323	4/1989	Papiernik	381/25
4,856,089	8/1989	Horton	455/351
4,864,619	9/1989	Spates	381/25
4,916,754	4/1990	Kang	2/12
4,951,316	8/1990	Moody	2/12
4,961,227	10/1990	LeDonne	381/24

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 495,056, Mar. 16, 1990.

[52] U.S. Cl. **D16/110**

[58] Field of Search **D16/103, 107, 110, 123; 351/44, 45, 47, 123, 156, 157; 2/10, 12, 13, 452, 454**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 210,424	3/1968	Mitchell	D16/110
D. 299,767	2/1989	Hsin	D16/110
2,474,386	6/1949	Volkman	179/156
2,638,593	5/1953	Eloranta	D16/110
2,810,022	10/1957	Finken et al.	179/156
3,696,357	10/1972	Kilgore	340/235
3,786,519	1/1974	Aileo	2/6
4,259,747	4/1981	Taesler et al.	2/6
4,403,120	9/1983	Yoshimi	179/182 R
4,456,797	6/1984	Olsen	179/156 R
4,551,584	11/1985	Mathiasen	179/156 R
4,565,258	1/1986	Butler et al.	181/129
4,638,207	1/1987	Radice	
4,682,363	7/1987	Goldfarb et al.	381/74
4,724,546	2/1988	Cumbie, Jr.	D16/110
4,727,599	2/1988	Rappaport et al.	455/351
4,776,044	10/1988	Makins	2/199
4,815,838	3/1989	Liautaud	2/12

OTHER PUBLICATIONS

Penwalt Corporation, KYNAR® Piezo Film Technical Manual, 1987, pp. 1-66.

Primary Examiner—Bernard Ansher

Assistant Examiner—R. Barkai


Attorney, Agent, or Firm—Knobbe, Martens, Olson & Bear

[57] **CLAIM**

The ornamental design for a combined visor and eye shield, as shown and described.

DESCRIPTION

FIG. 1 is a front, top and left side perspective view of a combined visor and eye shield showing my new design; FIG. 2 is a bottom perspective view thereof; FIG. 3 is a top plan view thereof; FIG. 4 is a right-side elevational view thereof; FIG. 5 is a front elevational view thereof; FIG. 6 is a left-side elevational view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is a rear elevational view thereof; FIG. 9 is a front perspective view of a modified embodiment of the design shown in FIGS. 1-8; FIG. 10 is a bottom perspective view thereof; FIG. 11 is a top plan view thereof; FIG. 12 is a right-side elevational view thereof; FIG. 13 is a front elevational view thereof; FIG. 14 is a left-side elevational view thereof; FIG. 15 is a bottom plan view thereof; and, FIG. 16 is a rear elevational view thereof.







Fig. 1

Fig. 2






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16