



US00D331024S

# United States Patent [19]

[11] Patent Number: **Des. 331,024**

DeRidder

[45] Date of Patent: **\*\* Nov. 17, 1992**

[54] **COMBINED TEMPERATURE AND HUMIDITY DETECTION INSTRUMENT**

2,571,628 10/1951 Stanley ..... D10/96  
3,771,364 11/1973 Worthington ..... 73/338 X  
3,855,863 12/1974 Kuehn et al. .... 73/336 X

[76] Inventor: **Peter H. DeRidder**, 5572 Swan Lake Dr., West Bloomfield, Mich. 48322

*Primary Examiner*—Donald P. Walsh  
*Assistant Examiner*—Antoine D. Davis  
*Attorney, Agent, or Firm*—Dykema Gossett

[\*\*] Term: **14 Years**

[57] **CLAIM**

[21] Appl. No.: **583,710**

The ornamental design for a combined temperature and humidity detection instrument, as shown and described.

[22] Filed: **Sep. 17, 1990**

[52] U.S. Cl. .... **D10/52; D10/49**

[58] Field of Search ..... D10/49, 50, 51, 52, D10/53; 73/338, 336; 374/141, 142, 143, 194, 208

**DESCRIPTION**

FIG. 1 is a top, front and left side perspective view of a combined temperature and humidity detection instrument showing my new design;

[56] **References Cited**


**U.S. PATENT DOCUMENTS**

D. 314,155 1/1991 Toivonen ..... D10/52

FIG. 2 is a top, rear and right side perspective view; and,

FIG. 3 is a top plan view thereof.

The bottom plan view being flat, plane and unadorned.






FIG. 1




FIG. 2




FIG. 3