



US00D331024S

United States Patent [19]

[11] Patent Number: **Des. 331,024**

DeRidder

[45] Date of Patent: **** Nov. 17, 1992**

[54] **COMBINED TEMPERATURE AND HUMIDITY DETECTION INSTRUMENT**

2,571,628 10/1951 Stanley D10/96
3,771,364 11/1973 Worthington 73/338 X
3,855,863 12/1974 Kuehn et al. 73/336 X

[76] Inventor: **Peter H. DeRidder**, 5572 Swan Lake Dr., West Bloomfield, Mich. 48322

Primary Examiner—Donald P. Walsh
Assistant Examiner—Antoine D. Davis
Attorney, Agent, or Firm—Dykema Gossett

[**] Term: **14 Years**

[57] **CLAIM**

[21] Appl. No.: **583,710**

The ornamental design for a combined temperature and humidity detection instrument, as shown and described.

[22] Filed: **Sep. 17, 1990**

[52] U.S. Cl. **D10/52; D10/49**

[58] Field of Search D10/49, 50, 51, 52, D10/53; 73/338, 336; 374/141, 142, 143, 194, 208

DESCRIPTION

FIG. 1 is a top, front and left side perspective view of a combined temperature and humidity detection instrument showing my new design;

[56] **References Cited**


U.S. PATENT DOCUMENTS

D. 314,155 1/1991 Toivonen D10/52

FIG. 2 is a top, rear and right side perspective view; and,

FIG. 3 is a top plan view thereof.

The bottom plan view being flat, plane and unadorned.






FIG. 1




FIG. 2




FIG. 3