



US00D331869S

**United States Patent** [19]**Batts et al.**[11] **Patent Number: Des. 331,869**[45] **Date of Patent: \*\* Dec. 22, 1992**[54] **ADJUSTABLE HANGER BODY**[75] Inventors: **John H. Batts**, East Grand Rapids;  
**Russell O. Blanchard**, Zeeland, both  
of Mich.[73] Assignee: **Batts, Inc.**, Zeeland, Mich.[\*\*] Term: **14 Years**[21] Appl. No.: **648,361**[22] Filed: **Jan. 31, 1991****Related U.S. Application Data**[63] Continuation-in-part of Ser. No. 582,596, Sep. 13, 1990,  
abandoned.[52] U.S. Cl. .... **D6/328; D6/326**[58] Field of Search ..... **D6/326, 328; 223/90,**  
**223/95, 96; 24/511**[56] **References Cited****U.S. PATENT DOCUMENTS**

|            |         |                     |        |
|------------|---------|---------------------|--------|
| D. 271,649 | 12/1983 | Batts et al. ....   | D6/326 |
| D. 284,427 | 7/1986  | Bredeweg .          |        |
| D. 299,086 | 12/1988 | Wilson .....        | D6/326 |
| D. 307,982 | 5/1990  | Duester .           |        |
| 695,924    | 3/1902  | Grotenhuis .....    | D6/326 |
| 3,767,092  | 10/1973 | Garrison et al. .   |        |
| 4,034,903  | 7/1977  | Batts .             |        |
| 4,194,274  | 3/1980  | Garrison .          |        |
| 4,295,585  | 10/1981 | Garrison .          |        |
| 4,716,634  | 1/1988  | Fan .....           | 223/91 |
| 4,729,498  | 3/1988  | Blanchard .         |        |
| 4,746,039  | 5/1988  | Batts et al. .      |        |
| 4,746,839  | 5/1988  | Batts et al. ....   | D6/326 |
| 4,759,480  | 7/1988  | Duester et al. .... | 223/96 |
| 4,826,056  | 5/1989  | Duester et al. .    |        |
| 4,884,727  | 12/1989 | Blanchard .         |        |


*Primary Examiner*—B. J. Bullock*Attorney, Agent, or Firm*—Price, Heneveld, Cooper, De  
Witt & Litton[57] **CLAIM**The ornamental design for an adjustable hanger body,  
as shown and described.**DESCRIPTION**FIG. 1 is a front, perspective view of an adjustable  
hanger body showing the new design;FIG. 2 is a front, perspective view thereof with one arm  
telescoped into the central portion of the hanger body;  
FIG. 3 is a fragmentary, right front elevational view  
thereof;FIG. 4 is a fragmentary, right rear elevational view  
thereof;

FIG. 5 is a fragmentary, right top plan view thereof;

FIG. 6 is a fragmentary, right bottom view thereof;

FIG. 7 is a left end elevational view of a clamp shown  
separately for ease of illustration;FIG. 8 is a front, perspective view of a second embodi-  
ment of the design of FIG. 1;FIG. 9 is a front, perspective view of FIG. 8 with one  
arm telescoped into the central portion of the hanger  
body;FIG. 10 is a fragmentary, right front elevational view of  
FIG. 8;FIG. 11 is a fragmentary, right rear elevational view of  
FIG. 8;

FIG. 12 is a fragmentary, top plan view of FIG. 8;

FIG. 13 is a fragmentary, bottom plan view of FIG. 8;  
and,FIG. 14 is a left end elevational view of a clamp shown  
separately for ease of illustration.The hanger body is symmetrical about a vertical center  
line with the right view being a mirror image of the left  
view.The clamps in FIGS. 1, 2, 8 and 9 are shown in the open  
position; all other views show the clamps in the closed  
position.




Fig. 1.







Fig. 2.




*Fig. 3.*




*Fig. 4.*




*Fig. 5.*




*Fig. 6.*




*Fig. 7.*




*Fig. 8.*




*Fig. 9.*



*Fig. 10.*




*Fig. 11.*



*Fig. 12.*



*Fig. 13.*



*Fig. 14.*