



US00D332135S

# United States Patent [19]

[11] Patent Number: **Des. 332,135**

Bonnell

[45] Date of Patent: **\*\* Dec. 29, 1992**

## [54] PLUMBING FIXTURE HANDLE

[75] Inventor: **Thomas A. Bonnell**, Sheboygan, Wis.

[73] Assignee: **Kohler Co.**, Kohler, Wis.

[\*\*] Term: **14 Years**

[21] Appl. No.: **639,954**

[22] Filed: **Jan. 11, 1991**

[52] U.S. Cl. .... **D23/252; D8/308**

[58] Field of Search ..... **D23/238-243, D23/250-254; D8/300, 301, 307-312; 4/191, 192; 16/118, 121**

## [56] References Cited

### U.S. PATENT DOCUMENTS

D. 72,243	3/1927	Shore .....	D23/238
D. 235,098	5/1975	Doman .....	D23/252
D. 241,440	9/1976	Doman .....	D23/252
D. 263,989	4/1982	Fleischmann et al. ....	D23/252
D. 263,990	4/1982	Fleischmann et al. ....	D23/252
D. 265,117	6/1982	Fleischmann et al. ....	D23/252
D. 280,008	8/1985	Miller et al. ....	D23/241
D. 285,106	8/1986	Yost .....	D23/252
D. 285,597	9/1986	Miller et al. ....	D23/242
D. 288,836	3/1987	Yost .....	D23/241
D. 289,676	5/1987	Evans et al. ....	D23/252
D. 290,496	6/1987	Ryan .....	D23/252
D. 318,717	7/1991	Spangler .....	D23/252
D. 318,901	8/1991	Rodstein .....	D23/242
D. 320,335	10/1991	Bengtson .....	D23/252
D. 325,772	4/1992	Carr .....	D23/252
D. 327,532	6/1992	Ko .....	D23/252
4,349,940	9/1982	Fleischmann et al. ....	D23/252 X

## OTHER PUBLICATIONS

Page 56 of a Harden catalog showing the 88 Series, undated, admitted prior art.

Pages 16 and 40 from a Kohler catalog showing the Antique and Flair handles, undated, admitted prior art.

Page 8 of a Vellely Brass catalog showing Model TDWX1030IPS, undated, admitted prior art.

*Primary Examiner*—James R. Largen

*Attorney, Agent, or Firm*—Quarles & Brady

## [57] CLAIM

The ornamental design for a plumbing fixture handle, as shown and described.

## DESCRIPTION

FIG. 1 is a perspective view taken from the top, front and left side of a plumbing fixture handle showing my new design;

FIG. 2 is a rear elevational view thereof, the front elevational view being the mirror image of the rear elevational view shown;

FIG. 3 is a left side elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a perspective view taken from the top, front and left side of a second embodiment thereof;


FIG. 7 is a rear elevational view thereof, the front elevational view being the mirror image of the rear elevational view shown;

FIG. 8 is a left side elevational view thereof;

FIG. 9 is a right side elevational view thereof; and,

FIG. 10 is a top plan view thereof.

The fragmentary broken line representations of screw slots in FIGS. 1, 5, 6, and 10, are for the purpose of illustration only.






FIG. 1

FIG. 2




FIG. 3




FIG. 4





FIG. 5




FIG. 6

FIG. 7




FIG. 8




FIG. 9





FIG. 10