



US00D332181S

United States Patent [19]

[11] Patent Number: Des. 332,181

Sacco et al.

[45] Date of Patent: ** Jan. 5, 1993

[54] VEHICLE SEAT

[75] Inventors: Bruno Sacco; Josef Gallitzendörfer, both of Sindelfingen, Fed. Rep. of Germany

[73] Assignee: Mercedes-Benz AG, Fed. Rep. of Germany

[**] Term: 14 Years

[21] Appl. No.: 561,592

[22] Filed: Aug. 2, 1990

[30] Foreign Application Priority Data

Feb. 2, 1990 [DE]	Fed. Rep. of Germany	9000770
[52] U.S. Cl.		D6/356
[58] Field of Search	D6/352, 366;	
	297/DIG. 1, DIG. 2, 153, 155, 250, 439, 445,	
	487	

[56] References Cited

U.S. PATENT DOCUMENTS

D. 273,540	4/1984	Wagner et al.	D6/356
D. 273,920	5/1984	Tixier	D6/356
D. 275,430	9/1984	Ochunder	D6/366
D. 278,869	5/1985	Bohl	D6/366
D. 280,472	10/1985	Seto	D6/356
D. 283,089	3/1986	McArdle	D6/356 X
D. 288,387	2/1987	Ochsner	D6/366
4,707,027	11/1987	Horvath et al.	D6/356 X

FOREIGN PATENT DOCUMENTS

104423	6/1982	Japan	297/417
156837	9/1984	Japan	297/487
164088	9/1984	Japan	297/DIG. 1

Primary Examiner—Carmen H. Vales-Lado
Assistant Examiner—Monica A. Hannon

Attorney, Agent, or Firm—Evenson, Wands, Edwards, Lenahan & McKeown

[57] CLAIM

The ornamental design for a vehicle seat, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a vehicle seat showing our new design thereof;
 FIG. 2 is a right side elevational view thereof;
 FIG. 3 is a left side elevational view thereof;
 FIG. 4 is a front perspective view thereof;
 FIG. 5 is a rear perspective view thereof;
 FIG. 6 is a front perspective view of a second embodiment of the vehicle seat shown in FIG. 1;
 FIG. 7 is a right side elevational view of FIG. 6 thereof;
 FIG. 8 is a left side elevational view of FIG. 6 thereof;
 FIG. 9 is a front perspective view of FIG. 6 thereof;
 FIG. 10 is a rear elevational view of FIG. 6 thereof;
 FIG. 11 is a front perspective view of a third embodiment of the vehicle seat shown in FIG. 1;
 FIG. 12 is a right side perspective view of FIG. 11 thereof;
 FIG. 13 is a left side perspective view of FIG. 11 thereof;
 FIG. 14 is a front perspective view of FIG. 11 thereof;
 FIG. 15 is a rear perspective view of FIG. 11 thereof;
 FIG. 16 is a front perspective view of a fourth embodiment of the vehicle seat shown in FIG. 1;
 FIG. 17 is a right side perspective view of FIG. 16 thereof;
 FIG. 18 is a left side perspective view of FIG. 16 thereof;
 FIG. 19 is a front perspective view of FIG. 16 thereof; and,
 FIG. 20 is a rear perspective view of FIG. 16 thereof.




Fig. 1





Fig. 2






Fig. 3

Fig. 4




Fig. 5




Fig. 6





Fig. 7






Fig. 8

Fig. 9




Fig. 10




Fig. 11





Fig. 12






Fig. 13

Fig. 14




Fig. 15




Fig. 16





Fig. 17






Fig. 18

Fig. 19




Fig. 20

