



US00D333084S

United States Patent [19]

Kanemitsu et al.

[11] Patent Number: Des. 333,084

[45] Date of Patent: ** Feb. 9, 1993

[54] PULLEY

[75] Inventors: Toshiaki Kanemitsu, Kobe; Kazuyuki Oda, Hyogo; Shuji Kanemitsu, Kobe, all of Japan

[73] Assignee: Kabushiki Kaisha Kanemitsu, Japan

[**] Term: 14 Years

[21] Appl. No.: 706,730

[22] Filed: May 29, 1991

[30] Foreign Application Priority Data

Dec. 12, 1990 [JP] Japan 2-41693

Dec. 19, 1990 [JP] Japan 2-42517

[52] U.S. Cl. D8/360

[58] Field of Search D8/360; 22/105; 29/159 R, 159.1; 474/169-170; 74/230.8; 72/105, 82

3,772,928 11/1973 Gobeille 74/230.7
3,838,485 10/1974 Oldford 29/159 R
3,907,371 9/1975 Luedi et al. 301/96
3,945,102 3/1976 Kotlar 29/159 R
3,953,995 5/1976 Haswell et al. 72/84
3,962,926 6/1976 Kotlar 74/230.8
3,977,264 8/1976 Sproul 74/230.8
3,994,181 11/1976 Sproul 74/230.8
4,050,321 9/1977 Kraft 74/230.8
4,059,023 11/1977 Sproul 74/230.3
4,078,410 3/1978 Lemmo 72/82
4,080,704 3/1978 Blakesley 29/159 R
4,083,215 4/1978 Guetzlaff 72/82
4,086,798 5/1978 Lemmo 72/82
4,197,756 4/1980 Yaros 74/230.3
4,273,547 6/1981 Bytzer 474/170
4,313,323 2/1982 Kanemitsu 72/84
4,455,853 6/1984 Kanemitsu 72/84
4,518,374 5/1985 Kanemitsu 474/170
4,525,595 6/1985 Harriman 174/35 GC
4,551,122 11/1985 Kraft et al. 474/170

[56] References Cited

U.S. PATENT DOCUMENTS

D. 266,982 11/1982 Kanemitsu D8/360
D. 266,983 11/1982 Kanemitsu D8/360
D. 266,984 11/1982 Kanemitsu D8/360
D. 267,472 1/1983 Kanemitsu D8/360
D. 267,540 1/1983 Kanemitsu D8/360
D. 267,541 1/1983 Kanemitsu D8/360
D. 268,092 3/1983 Kanemitsu D8/360
D. 275,176 8/1984 Kanemitsu D8/360
D. 275,365 9/1984 Kanemitsu D8/360
D. 276,409 11/1984 Kanemitsu D8/360
D. 277,547 2/1985 Kanemitsu D8/360
D. 294,675 3/1988 Kanemitsu D8/360
D. 297,707 9/1988 Kanemitsu D8/360
D. 308,012 5/1990 Kanemitsu D8/360
D. 308,013 5/1990 Kanemitsu D8/360
D. 313,932 1/1991 Kanemitsu D8/360
D. 317,709 6/1991 Kanemitsu D8/360
D. 320,927 10/1991 Kanemitsu D8/360
2,139,833 12/1938 Jeune et al. 29/159.1
2,471,906 5/1949 Smith 74/230.3
2,656,730 10/1953 Mitchell 74/230.8
2,787,914 4/1957 Nelson 74/230.8
2,878,551 3/1959 Woodward 29/159.1
3,368,376 2/1968 Previte 72/82
3,457,751 7/1969 Lindeman 72/105
3,722,309 3/1973 Shaffer 74/230.8

FOREIGN PATENT DOCUMENTS

2822056 11/1979 Fed. Rep. of Germany .
5081276 1/1955 Italy .
32-90459 6/1957 Japan .
32-195551 12/1957 Japan .
33-128564 8/1958 Japan .
33-163538 9/1958 Japan .
34-13535 1/1959 Japan .
5411260 3/1959 Japan .
56143863 11/1959 Japan .

Primary Examiner—Wallace R. Burke

Assistant Examiner—H. Baynham

Attorney, Agent, or Firm—Jones, Tullar & Cooper

[57] CLAIM

The ornamental design for a pulley, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a pulley showing our new design with the rear and side elevational views being mirror images;

FIG. 2 is a top plan view thereof with the bottom plan view being a mirror image thereof;

FIG. 3 is a sectional view thereof taken along line 3—3 of FIG. 2;




FIG. 4 is a front elevational view of a second embodiment of the design shown in FIG. 1 with the rear and side elevational views being mirror images;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a sectional view thereof taken along line 7—7 of FIG. 5;

FIG. 8 is a front elevational view of a third embodiment

of the design shown in FIG. 1 with the rear and side elevational views being mirror images;

FIG. 9 is a top plan view thereof with the bottom plan view being a mirror image thereof; and,

FIG. 10 is a sectional view thereof taken along line 10—10 of FIG. 9.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10