



US00D333120S

United States Patent [19]

[11] Patent Number: **Des. 333,120**

Shimoo et al.

[45] Date of Patent: **** Feb. 9, 1993**

[54] BATTERY CHARGER

[75] Inventors: **Kuniyuki Shimoo, Hyogo; Kazuo Takada, Nara, both of Japan**

[73] Assignee: **Sanyo Electric Co., Ltd., Osaka, Japan**

[**] Term: **14 Years**

[21] Appl. No.: **688,075**

[22] Filed: **Apr. 19, 1991**

[30] Foreign Application Priority Data

Oct. 19, 1990 [JP] Japan 2-35220

[52] U.S. Cl. **D13/107**

[58] Field of Search **D13/107, 108; D14/240; 320/2, 3, 4, 5**

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 247,619 3/1978 Edgell et al. D13/107 X
- D. 328,276 7/1992 Koinuma D13/107
- 5,019,767 5/1991 Shirai et al. 320/2

OTHER PUBLICATIONS

Battery chargers on p. 428 of B.A. Pargh 1989 Catalog. Battery chargers on p. 199 of Hong Hong Enterprise Feb. 1990.

Primary Examiner—Wallace R. Burke
Assistant Examiner—Joel Sincavage
Attorney, Agent, or Firm—Darby & Darby

[57] CLAIM

The ornamental design for a battery charger, as shown and described.

DESCRIPTION

FIG. 1 is a front and upper right perspective view of a battery charger showing our new design; FIG. 2 is a top plan view thereof; FIG. 3 is a bottom plan view thereof; FIG. 4 is a left side elevational view thereof; FIG. 5 is a right side elevational view thereof; FIG. 6 is a front elevational view thereof; FIG. 7 is a rear elevational view thereof; and, FIG. 8 is a rear elevational view thereof with the plug extended.




FIG. 1




FIG. 3




FIG. 2




FIG. 6




FIG. 4




FIG. 5




FIG. 7




FIG. 8

