



US00D333643S

**United States Patent** [19]  
**Maxwell**

[11] **Patent Number: Des. 333,643**

[45] **Date of Patent: \*\* Mar. 2, 1993**

[54] **PNEUMATIC TIRE TREAD AND BUTTRESS**

[75] **Inventor: Paul B. Maxwell, Stow, Ohio**

[73] **Assignee: The Goodyear Tire & Rubber Company, Akron, Ohio**

[\*\*] **Term: 14 Years**

[21] **Appl. No.: 538,948**

[22] **Filed: Jun. 14, 1990**

[52] **U.S. Cl. .... D12/147**

[58] **Field of Search ..... D12/141-151,  
D12/136; 152/209 R, 209 A, 209 B, 209 D**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 54,599	3/1920	Clarke	.....	D12/144
D. 310,804	9/1990	Covert et al.	.....	D12/147
4,700,762	10/1987	Landers	.....	152/209 R

**OTHER PUBLICATIONS**

Tires-TBA Merchandising, Jun. 1957, p. 60, Triple-S-ervice Tire, lower left side of page.

1990 Tread Design Guide, p. 42, Hoosier Dirt Bozz, second row down from top, left side of page.

*Primary Examiner*—James M. Gandy

*Attorney, Agent, or Firm*—T. P. Lewandowski


[57] **CLAIM**

The ornamental design for a pneumatic tire tread and buttress, as shown and described.

**DESCRIPTION**

FIG. 1 is a front elevation view of a pneumatic tire tread and buttress showing my new design, it being understood that the pattern is repeated uniformly throughout the circumference of the tread and buttress; FIG. 2 is a right side elevational view of FIG. 1; and, FIG. 3 is a left side elevational view of FIG. 1.

The broken line showing of environmental structure in FIGS. 2 and 3 of the drawing is for illustrative purposes only and forms no part of the claimed design.






FIG-1




FIG-2




FIG-3