



US00D333643S

United States Patent [19]
Maxwell

[11] **Patent Number: Des. 333,643**
[45] **Date of Patent: ** Mar. 2, 1993**

[54] **PNEUMATIC TIRE TREAD AND BUTTRESS**

[75] **Inventor: Paul B. Maxwell, Stow, Ohio**

[73] **Assignee: The Goodyear Tire & Rubber Company, Akron, Ohio**

[**] **Term: 14 Years**

[21] **Appl. No.: 538,948**

[22] **Filed: Jun. 14, 1990**

[52] **U.S. Cl. D12/147**

[58] **Field of Search D12/141-151, D12/136; 152/209 R, 209 A, 209 B, 209 D**

[56] **References Cited**

U.S. PATENT DOCUMENTS

- D. 54,599 3/1920 Clarke D12/144
- D. 310,804 9/1990 Covert et al. D12/147
- 4,700,762 10/1987 Landers 152/209 R

OTHER PUBLICATIONS

Tires-TBA Merchandising, Jun. 1957, p. 60, Triple-S-ervice Tire, lower left side of page.

1990 Tread Design Guide, p. 42, Hoosier Dirt Bozz, second row down from top, left side of page.

Primary Examiner—James M. Gandy

Attorney, Agent, or Firm—T. P. Lewandowski


[57] **CLAIM**

The ornamental design for a pneumatic tire tread and buttress, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of a pneumatic tire tread and buttress showing my new design, it being understood that the pattern is repeated uniformly throughout the circumference of the tread and buttress; FIG. 2 is a right side elevational view of FIG. 1; and, FIG. 3 is a left side elevational view of FIG. 1.

The broken line showing of environmental structure in FIGS. 2 and 3 of the drawing is for illustrative purposes only and forms no part of the claimed design.






FIG-1




FIG-2




FIG-3