



US00D333995S

United States Patent [19]

[11] Patent Number: **Des. 333,995**

Potts et al.

[45] Date of Patent: **** Mar. 16, 1993**

[54] **COMBINED TILT MONITOR AND SIGNAL FOR VEHICLE**

4,500,868 2/1985 Tokitsu .
4,528,547 7/1985 Rodney .
5,051,735 9/1991 Furukawa 340/905

[76] Inventors: **Danny Potts; Kurt Mullins**, both of
3400 LaMesa Way, South Sioux
City, Nebr. 68776

Primary Examiner—Wallace R. Burke
Assistant Examiner—Marcus Jackson
Attorney, Agent, or Firm—Terry M. Gernstein

[**] Term: **14 Years**

[57] **CLAIM**

[21] Appl. No.: **556,987**

The ornamental design for a combined tilt monitor and signal for vehicle, as shown and described.

[22] Filed: **Jul. 25, 1990**

[52] U.S. Cl. **D10/104**

[58] Field of Search D10/104, 106, 121, 114,
D10/98; 340/467, 905, 901, 902, 903, 904, 440


DESCRIPTION

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 180,845 8/1957 Rintelmann D10/98
3,711,828 1/1973 Hawkins 340/467
4,240,152 12/1980 Duncan et al. 340/901
4,345,238 8/1982 Weir .

FIG. 1 is a perspective view of a combined tilt monitor and signal for vehicles showing our new design; FIG. 2 is a front elevational view therefor, with the rear;
FIG. 3 is a top plan view thereof, with the bottom being plain and unornamented;
FIG. 4 is a right side elevational view thereof; and, FIG. 5 is a left side elevational view thereof.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5