



US00D334623S

United States Patent [19]

[11] Patent Number: **Des. 334,623**

Burton et al.

[45] Date of Patent: **** Apr. 6, 1993**

- [54] **TRACTION UNIT FOR REMOVING LOADING FROM THE BACK**
- [75] Inventors: **Charles V. Burton, Excelsior; Gregory K. Peterson, North Oaks; Casey L. Carlson, Edina; Jeffrey A. Weber; William E. Stumpf, both of Minneapolis, all of Minn.**
- [73] Assignee: **Spinal Designs International, Inc., Minneapolis, Minn.**
- [**] Term: **14 Years**
- [21] Appl. No.: **473,686**
- [22] Filed: **Feb. 1, 1990**
- [52] U.S. Cl. **D24/188**
- [58] Field of Search **D24/188; 128/78, 83.5, 128/68, 75, 79; 602/36, 19**

4,688,557	8/1987	Bradstreet	128/71
4,715,362	12/1987	Scott	128/75
4,725,055	2/1988	Skowronski	272/134
4,746,116	5/1988	Inada	272/144
4,854,305	8/1989	Bremer	128/75
4,881,528	11/1989	Scott	128/75
5,033,459	7/1991	Burton	128/71
5,088,476	2/1992	Burton	606/241
5,105,803	4/1992	Burton	602/36

FOREIGN PATENT DOCUMENTS

980199	12/1975	Canada	.
2363390	6/1975	Fed. Rep. of Germany	.
3104832A1	1/1983	Fed. Rep. of Germany	.
3420858A1	12/1985	Fed. Rep. of Germany	.
1371332	7/1964	France	.
797664	1/1981	U.S.S.R.	.
812280	3/1981	U.S.S.R.	.
WO80/01540	8/1980	World Int. Prop. O.	.
WO89/10732	11/1989	World Int. Prop. O.	.

[56] **References Cited**
U.S. PATENT DOCUMENTS

D. 296,590	7/1988	Cottrell	D24/188
D. 310,882	9/1990	Pope	D24/188
1,356,365	10/1920	Hosmer	.
2,984,238	5/1961	Axtell et al.	128/75
3,103,357	9/1963	Berne	272/79
3,167,068	1/1965	Carr	128/75
3,353,532	11/1967	Ellis	128/75
3,396,012	8/1983	Cobiski	128/75
4,030,489	6/1977	Buckner	128/75
4,205,665	6/1980	Burton	128/68
4,269,179	5/1981	Burton et al.	128/75
4,422,452	12/1983	Burton	128/75
4,515,152	5/1985	Teeter	128/75
4,569,340	2/1986	Burton	128/75
4,583,533	4/1986	Goodley et al.	128/75
4,603,689	8/1986	Horner	128/75
4,617,919	10/1986	Suhre	128/78

Primary Examiner—Stella Reid
Attorney, Agent, or Firm—Merchant, Gould, Smith, Edell, Welter & Schmidt

[57] CLAIM

The ornamental design for a traction unit for removing loading from the back, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a traction unit for removing loading from the back, showing our new design;
 FIG. 2 is a top plan view thereof;
 FIG. 3 is a front elevational view thereof;
 FIG. 4 is a bottom plan view thereof;
 FIG. 5 is a right side elevational view thereof;
 FIG. 6 is a left side elevational view thereof; and,
 FIG. 7 is a rear elevational view thereof.





FIG. 1






FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7