



US00D334893S

United States Patent [19]

[11] Patent Number: **Des. 334,893**

Cunningham

[45] Date of Patent: **** Apr. 20, 1993**

[54] **LINE CURRENT VARIATION INDICATOR**

[76] Inventor: **Scott E. Cunningham, P.O. Box 13272, Mexico Beach, Fla. 32410**

[**] Term: **14 Years**

[21] Appl. No.: **781,275**

[22] Filed: **Oct. 23, 1991**

[52] U.S. Cl. **D10/75**

[58] Field of Search **D10/75, 78, 46; 324/127, 133, 156, 173; 340/815.24, 815.26, 815.31**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 276,028	10/1984	Crotty et al.	D10/75
D. 281,401	11/1985	Perrins	D10/75
3,594,767	7/1971	Link	324/133
4,587,590	5/1986	Bala .	
4,591,942	3/1986	Willard .	

4,733,321 3/1988 Lindeperg .


Primary Examiner—Alan P. Douglas
Assistant Examiner—Antoine D. Davis
Attorney, Agent, or Firm—Terry M. Gernstein

[57] **CLAIM**

The ornamental design for a line current variation indicator, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the line current variation indicator embodying the design of the present invention;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a rear elevational view thereof.
FIG. 4 is a an end elevational view thereof, the end opposite being a mirror image of the end shown in FIG. 4; and,
FIG. 5 is a top plan view thereof, the bottom being unadorned.






FIG.1.




FIG. 2.




FIG. 4.




FIG. 3




FIG. 5.