



US00D334909S

# United States Patent [19]

[11] Patent Number: **Des. 334,909**

Brayer et al.

[45] Date of Patent: **\*\* Apr. 20, 1993**

[54] **PNEUMATIC TIRE TREAD AND BUTTRESS**

[75] Inventors: **Randall R. Brayer**, Uniontown;  
**Warren L. Croyle**, Akron, both of  
Ohio; **Maurice Graas**, Reichlange,  
Luxembourg

[73] Assignee: **The Goodyear Tire & Rubber  
Company**, Akron, Ohio

[\*\*] Term: **14 Years**

[21] Appl. No.: **736,186**

[22] Filed: **Jul. 26, 1991**

### Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 484,731, Feb. 20, 1990,  
abandoned.

[52] U.S. Cl. .... **D12/147**

[58] Field of Search ..... **D12/136, 137, 138, 140,  
D12/145-151; 152/209 R, 209 A, 209 B, 209 D**

### [56] References Cited

#### U.S. PATENT DOCUMENTS

- D. 315,128 3/1991 Graas et al. .... D12/147
- D. 315,129 3/1991 Graas et al. .... D12/147
- D. 316,991 5/1991 Graas ..... D12/147

#### FOREIGN PATENT DOCUMENTS

- 0296605 12/1988 European Pat. Off. .
- 3815829 12/1988 Fed. Rep. of Germany .
- 0204804 8/1989 Japan ..... 152/209 A


*Primary Examiner*—James M. Gandy  
*Attorney, Agent, or Firm*—T. P. Lewandowski

### [57] CLAIM

The ornamental design for a pneumatic tire tread and buttress, as shown and described.

### DESCRIPTION

FIG. 1 is a perspective view of a pneumatic tire tread and buttress showing our new design;  
 FIG. 2 is a front elevational view thereof;  
 FIG. 3 is a fragmentary elevational view of the side opposite to that shown in FIG. 1;  
 FIG. 4 is a perspective view of a pneumatic tire tread and buttress showing a second embodiment of our new design;  
 FIG. 5 is a front elevational view of the embodiment of FIG. 4;  
 FIG. 6 is a side elevational view of the embodiment of FIG. 4, the opposite side being substantially a mirror image thereof; and,  
 FIG. 7 is a front elevational view of a pneumatic tire tread and buttress showing a third embodiment of our new design which differs from the second embodiment only in the omission of the circumferential row of blocks adjacent to the right shoulder ribs.  
 The pattern is understood to be repeated uniformly throughout the circumferences of all three embodiments of the pneumatic tire tread and buttress.  
 The broken line showing of the tire sidewall in all seven views of the drawing is for illustrative purposes only and forms no part of the claimed design.








FIG. 1



**FIG. 2**



**FIG. 3**




FIG-4




FIG-5




FIG-6




FIG-7