



US00D336281S

United States Patent [19]

Nakamura et al.

[11] Patent Number: Des. 336,281

[45] Date of Patent: ** Jun. 8, 1993

[54] BATTERY CHARGER

[75] Inventors: Mitsuhiro Nakamura; Toshihisa Yokoi, both of Tokyo, Japan

[73] Assignee: Sony Corporation, Tokyo, Japan

[**] Term: 14 Years

[21] Appl. No.: 779,616

[22] Filed: Oct. 21, 1991

[30] Foreign Application Priority Data

May 30, 1991 [JP]	Japan	3-15742
[52] U.S. Cl.		D13/107
[58] Field of Search	D13/107, 108; D14/240;	320/2, 3, 4, 5

[56] References Cited

U.S. PATENT DOCUMENTS

4,636,703	1/1987	Tohya et al.	D13/107 X
4,766,361	8/1988	Pusateri	320/2
5,057,761	10/1991	Felegyhazi, Sr.	320/2

OTHER PUBLICATIONS

Eveready battery charger Rf2, 1989 publication.
Eveready battery charger FCC2, 1989 publication.

Primary Examiner—Wallace R. Burke
Assistant Examiner—Joel Sincavage
Attorney, Agent, or Firm—Lewis H. Eslinger; Jay H. Maioli

[57] CLAIM

The ornamental design for a battery charger, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a battery charger showing our new design;
 FIG. 2 is a right-side elevational view thereof;
 FIG. 3 is a left-side elevational view thereof;
 FIG. 4 is a top plan view thereof;
 FIG. 5 is a bottom plan view thereof. The broken line showing is included for the purpose of illustrating environmental elements only and forms no part of the claimed design;
 FIG. 6 is a front and upper right perspective view thereof, shown in the open position; and,
 FIG. 7 is a front and upper right perspective view thereof.





FIG. 1




FIG. 2




FIG. 3




FIG. 4

FIG. 5




FIG. 7




FIG. 6

