



US00D336281S

# United States Patent [19]

[11] Patent Number: **Des. 336,281**

Nakamura et al.

[45] Date of Patent: **\*\* Jun. 8, 1993**

## [54] BATTERY CHARGER

[75] Inventors: **Mitsuhiro Nakamura; Toshihisa Yokoi**, both of Tokyo, Japan

[73] Assignee: **Sony Corporation**, Tokyo, Japan

[\*\*] Term: **14 Years**

[21] Appl. No.: **779,616**

[22] Filed: **Oct. 21, 1991**

### [30] Foreign Application Priority Data

May 30, 1991 [JP] Japan ..... 3-15742

[52] U.S. Cl. .... **D13/107**

[58] Field of Search ..... **D13/107, 108; D14/240; 320/2, 3, 4, 5**

### [56] References Cited

#### U.S. PATENT DOCUMENTS

4,636,703 1/1987 Tohya et al. .... **D13/107 X**

4,766,361 8/1988 Pusateri ..... 320/2

5,057,761 10/1991 Felegyhazi, Sr. .... 320/2

## OTHER PUBLICATIONS

Eveready battery charger Rf2, 1989 publication.

Eveready battery charger FCC2, 1989 publication.

*Primary Examiner*—Wallace R. Burke

*Assistant Examiner*—Joel Sincavage

*Attorney, Agent, or Firm*—Lewis H. Eslinger; Jay H. Maioli

## [57] CLAIM

The ornamental design for a battery charger, as shown and described.

## DESCRIPTION

FIG. 1 is a front elevational view of a battery charger showing our new design;

FIG. 2 is a right-side elevational view thereof;



FIG. 3 is a left-side elevational view thereof;

FIG. 4 is a top plan view thereof;


FIG. 5 is a bottom plan view thereof. The broken line showing is included for the purpose of illustrating environmental elements only and forms no part of the claimed design;

FIG. 6 is a front and upper right perspective view thereof, shown in the open position; and,


FIG. 7 is a front and upper right perspective view thereof.




*FIG. 1*



*FIG. 2*




*FIG. 3*




*FIG. 4*

*FIG. 5*



*FIG. 7*



*FIG. 6*

