



US00D336281S

United States Patent [19]

Nakamura et al.

[11] Patent Number: **Des. 336,281**

[45] Date of Patent: **** Jun. 8, 1993**

[54] BATTERY CHARGER

[75] Inventors: **Mitsuhiro Nakamura; Toshihisa Yokoi**, both of Tokyo, Japan

[73] Assignee: **Sony Corporation**, Tokyo, Japan

[**] Term: **14 Years**

[21] Appl. No.: **779,616**

[22] Filed: **Oct. 21, 1991**

[30] Foreign Application Priority Data

May 30, 1991 [JP] Japan 3-15742

[52] U.S. Cl. **D13/107**

[58] Field of Search **D13/107, 108; D14/240; 320/2, 3, 4, 5**

[56] References Cited

U.S. PATENT DOCUMENTS

4,636,703 1/1987 Tohya et al. **D13/107 X**

4,766,361 8/1988 Pusateri 320/2

5,057,761 10/1991 Felegyhazi, Sr. 320/2

OTHER PUBLICATIONS

Eveready battery charger Rf2, 1989 publication.

Eveready battery charger FCC2, 1989 publication.

Primary Examiner—Wallace R. Burke

Assistant Examiner—Joel Sincavage

Attorney, Agent, or Firm—Lewis H. Eslinger; Jay H. Maioli

[57] CLAIM

The ornamental design for a battery charger, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a battery charger showing our new design;

FIG. 2 is a right-side elevational view thereof;

FIG. 3 is a left-side elevational view thereof;

FIG. 4 is a top plan view thereof;

FIG. 5 is a bottom plan view thereof. The broken line showing is included for the purpose of illustrating environmental elements only and forms no part of the claimed design;

FIG. 6 is a front and upper right perspective view thereof, shown in the open position; and,

FIG. 7 is a front and upper right perspective view thereof.





FIG. 1




FIG. 2




FIG. 3




FIG. 4

FIG. 5




FIG. 7




FIG. 6

