



US00D338340S

United States Patent [19]

[11] Patent Number: Des. 338,340

Burks

[45] Date of Patent: ** Aug. 17, 1993

[54] RUNNER'S COMBINED WRITING PAD,
PENCIL AND RECORDER POUCH

FOREIGN PATENT DOCUMENTS

2559040 8/1985 France D3/106

[76] Inventor: Rufus W. Burks, 620 Sheridan St.
#307, Hyattsville, Md. 20783-3206

Primary Examiner—A. Hugo Word
Assistant Examiner—Doris V. Coles
Attorney, Agent, or Firm—Jacobson, Price, Holman &
Stern

[**] Term: 14 Years

[57] CLAIM

[21] Appl. No.: 797,817

The ornamental design for a runner's combined writing pad, pencil and recorder pouch, as shown and described.

[22] Filed: Nov. 26, 1991

[52] U.S. Cl. D3/106

[58] Field of Search D3/106, 100, 56, 58;
D2/630; 224/919, 242, 904, 240, 224, 229, 901,
251, 223, 236, 253


DESCRIPTION

[56] References Cited

U.S. PATENT DOCUMENTS

D. 288,263	2/1987	Pagano	D3/56
D. 290,185	6/1987	Di Cavalcante	D2/630
D. 293,387	12/1987	Wagner, II	D2/630
D. 312,351	11/1990	Bishop	D3/58
D. 318,374	7/1991	Powell	D3/56 X
814,205	3/1906	Hawes	D3/56 X
1,171,234	2/1916	O'Hara	D3/58 X
1,745,590	2/1930	Stanger	224/205 X
2,315,095	3/1943	Rhodes	224/228 X
4,119,249	10/1978	Hanson	224/253 X
4,284,220	8/1981	Nice	224/242
4,569,465	2/1986	O'Farrell	224/224
4,570,688	2/1986	Williams	150/102 X
4,645,105	2/1987	Plumbridge	224/269
4,699,303	10/1987	Kline	224/252
4,705,086	11/1987	O'Neill	150/134
4,744,497	5/1988	O'Neal	224/202
4,801,059	1/1989	Hayes	224/240
4,893,739	1/1990	Conner	224/240
4,998,653	3/1991	LaBelle	224/253 X

FIG. 1 is a front elevational view of a runner's combined pad, pencil and recorder pouch, showing my new design;
FIG. 2 is a top view thereof;
FIG. 3 is a bottom view thereof;
FIG. 4 is a rear elevational view thereof;
FIG. 5 is a left side view thereof;
FIG. 6 is a right side view thereof;
FIG. 7 is a front elevational view in the fully open position;
FIG. 8 is a top view thereof;
FIG. 9 is a bottom view thereof;
FIG. 10 is a left side view thereof;
FIG. 11 is a rear elevational view thereof;
FIG. 12 is a right side view thereof;
FIG. 13 is a front elevational view of the invention illustrated in FIG. 1, with the top portion open for use;
FIG. 14 is a front elevational view of a second embodiment;
FIG. 15 is a rear elevational view of the embodiment illustrated in FIG. 14; and,
FIG. 16 is a front elevational view in the closed position of the embodiment illustrated in FIG. 14.






FIG. 1



FIG. 2



FIG. 3




FIG. 4



FIG. 6



FIG. 5

FIG. 7




FIG. 8




FIG. 9



FIG. 12




FIG. 10

FIG. 11



FIG. 13





FIG. 14






FIG. 15




FIG. 16