

## US00D338880S

## United States Patent [19]

## Mizusugi et al.

[11] Patent Number: Des. 338,880

[45] Date of Patent: \*\* Aug. 31, 1993

[54]	COMPUTER	
[75]	Inventors:	Kanji Mizusugi, Mei; Kensho Tuji; Hiroshi Yamamizu, both of Nara, all of Japan
[73]	Assignee:	Sharp Kabushiki Kaisha, Osaka, Japan
[**]	Term:	14 Years
[21]	Appl. No.:	734,812
[22]	Filed:	Jul. 23, 1991
[30] Foreign Application Priority Data		
Jan [52]	U.S. Cl Field of Sea D14/11:	P] Japan
[56]		References Cited
	U.S. I	PATENT DOCUMENTS
	_	1988 Kagayama et al D14/100

Primary Examiner—Wallace R. Burke Assistant Examiner—Freda S. Nunn Attorney, Agent, or Firm—Nixon & Vanderhye

[57] CLAIM

The ornamental design for a computer, as shown and described.

## DESCRIPTION

FIG. 1 is a top, front and right side perspective view of a computer according to the present invention and illustrated in the open position;

FIG. 2 is a front elevational view thereof in the closed position;

FIG. 3 is a top plan view thereof in the closed position; FIG. 4 is rear elevational view thereof in the closed position;

FIG. 5 is a bottom plan view thereof in the closed position;

FIG. 6 is a right side elevational view thereof in the closed position, with the left side elevational view thereof being the mirror-image;

FIG. 7 is a right side elevational view of the computer thereof in the open position;

FIG. 8 is a front elevational view of the computer thereof in the open position;

FIG. 9 is a top plan view of the computer thereof in the open position;

FIG. 10 is a rear elevational view of the computer thereof in the open position;

FIG. 11 is a bottom plan view of the computer thereof in the open position;

FIG. 12 is a top, front and right side perspective view of a second embodiment of a computer according to the present invention, illustrated in the open condition;

FIG. 13 is a top plan view thereof in the closed position; FIG. 14 is a right side elevational view thereof in the closed position with the left side elevational view being the mirror-image thereof;

FIG. 15 is a right side elevational view thereof illustrated in the open position with the left side elevational view being the mirror image thereof;


FIG. 12 in the energition thereof:

FIG. 12 in the open position thereof;


FIG. 17 is a top plan view thereof in the open position; FIG. 18 is a rear elevational view of the embodiment thereof illustrated in FIG. 12; and,

FIG. 19 is a bottom plan view of the embodiment thereof illustrated in FIG. 12.

The bottom plan and front and rear elevational views of the embodiment illustrated in FIG. 12 correspond to the bottom plan and front and rear elevational views of the embodiment thereof illustrated in FIG. 1.



Aug. 31, 1993






FIG. 2




FIG. 3





FIG. 5



Aug. 31, 1993

FIG. 6




FIG. 7

FIG. 8





FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

Aug. 31, 1993




FIG. 15

