



US00D339560S

United States Patent [19]

[11] Patent Number: Des. 339,560

Byrd

[45] Date of Patent: ** Sep. 21, 1993

[54] **VEHICLE FLOOR MAT WITH WARNING INDICIA**

[76] Inventor: Darrel W. Byrd, P.O. Box 699, Jackson, Calif. 95642

[**] Term: 14 Years

[21] Appl. No.: 841,457

[22] Filed: Feb. 27, 1992

[52] U.S. Cl. D12/203; D12/185; D6/583; D10/109

[58] Field of Search D12/203, 185; D10/109; D6/582, 583; 296/97.23; 15/215, 217; 280/851; 40/591, 597

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 85,859	12/1931	Capouch	D6/583
D. 200,524	3/1965	Narens	D6/583
D. 244,369	5/1977	Sample	D12/203
D. 310,000	8/1990	Livingstone et al.	D6/583
2,546,781	3/1951	Rheeling	280/851
3,582,108	6/1971	Carlton	280/851
5,031,347	7/1991	Berg	40/591
5,156,274	10/1992	Williams, Jr. et al.	40/591

FOREIGN PATENT DOCUMENTS

0222713 5/1987 European Pat. Off. 296/136


Primary Examiner—James M. Gandy
Attorney, Agent, or Firm—Lothrop & West

[57] **CLAIM**

The ornamental design for a vehicle floor mat with warning indicia, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a vehicle floor mat with warning indicia, showing my new design, with the multiple suction cup strip in folded position;
 FIG. 2 is a perspective view thereof, with the multiple suction cup strip in extended, operative position;
 FIG. 3 is a front elevational view thereof;
 FIG. 4 is a rear elevational view thereof;
 FIG. 5 is an elevational view of one lateral edge thereof, the opposite lateral edge being a mirror image;
 FIG. 6 is an elevational view of the top end thereof;
 FIG. 7 is an elevational view of the bottom end thereof;
 FIG. 8 is a front elevational view thereof with the multiple suction cup strip in extended, operative position;
 FIG. 9 is a rear elevational view of FIG. 8;
 FIG. 10 is a perspective view of a vehicle floor mat with warning indicia showing a second embodiment of my new design, with the multiple suction cup strip in folded position, and wherein the warning indicia resides in diagonal alternating reflective stripes of red and silver;
 FIG. 11 is a front elevational view of the embodiment of FIG. 10;
 FIG. 12 is a rear elevational view of the embodiment of FIG. 10;
 FIG. 13 is an elevational view of one lateral edge of the embodiment of FIG. 10, the opposite lateral edge being a mirror image;
 FIG. 14 is an elevational view of the top end of the embodiment of FIG. 10;
 FIG. 15 is an elevational view of the bottom end of the embodiment of FIG. 10;
 FIG. 16 is a front elevational view of the embodiment of FIG. 10 with the multiple suction cup strip in extended operative position; and,
 FIG. 17 is a rear elevational view of FIG. 16.






FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13




FIG. 14



FIG. 15




FIG. 16




FIG. 17