



US00D339560S

United States Patent [19]

Byrd

[11] Patent Number: Des. 339,560

[45] Date of Patent: ** Sep. 21, 1993

[54] VEHICLE FLOOR MAT WITH WARNING INDICIA

[76] Inventor: Darrel W. Byrd, P.O. Box 699, Jackson, Calif. 95642

[**] Term: 14 Years

[21] Appl. No.: 841,457

[22] Filed: Feb. 27, 1992

[52] U.S. Cl. D12/203; D12/185; D6/583; D10/109

[58] Field of Search D12/203, 185; D10/109; D6/582, 583; 296/97.23; 15/215, 217; 280/851; 40/591, 597

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|---------------------------|---------|
| D. 85,859 | 12/1931 | Capouch | D6/583 |
| D. 200,524 | 3/1965 | Narens | D6/583 |
| D. 244,369 | 5/1977 | Sample | D12/203 |
| D. 310,000 | 8/1990 | Livingstone et al. | D6/583 |
| 2,546,781 | 3/1951 | Rheeling | 280/851 |
| 3,582,108 | 6/1971 | Carlton | 280/851 |
| 5,031,347 | 7/1991 | Berg | 40/591 |
| 5,156,274 | 10/1992 | Williams, Jr. et al. | 40/591 |

FOREIGN PATENT DOCUMENTS

0222713 5/1987 European Pat. Off. 296/136

Primary Examiner—James M. Gandy
Attorney, Agent, or Firm—Lothrop & West

[57]

CLAIM

The ornamental design for a vehicle floor mat with warning indicia, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a vehicle floor mat with warning indicia, showing my new design, with the multiple suction cup strip in folded position;

FIG. 2 is a perspective view thereof, with the multiple suction cup strip in extended, operative position;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is an elevational view of one lateral edge thereof, the opposite lateral edge being a mirror image;

FIG. 6 is an elevational view of the top end thereof;

FIG. 7 is an elevational view of the bottom end thereof;

FIG. 8 is a front elevational view thereof with the multiple suction cup strip in extended, operative position;

FIG. 9 is a rear elevational view of FIG. 8;

FIG. 10 is a perspective view of a vehicle floor mat with warning indicia showing a second embodiment of my new design, with the multiple suction cup strip in folded position, and wherein the warning indicia resides in diagonal alternating reflective stripes of red and silver;

FIG. 11 is a front elevational view of the embodiment of FIG. 10;

FIG. 12 is a rear elevational view of the embodiment of FIG. 10;


FIG. 13 is an elevational view of one lateral edge of the embodiment of FIG. 10, the opposite lateral edge being a mirror image;

FIG. 14 is an elevational view of the top end of the embodiment of FIG. 10;

FIG. 15 is an elevational view of the bottom end of the embodiment of FIG. 10;

FIG. 16 is a front elevational view of the embodiment of FIG. 10 with the multiple suction cup strip in extended operative position; and,

FIG. 17 is a rear elevational view of FIG. 16.






FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5



FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13




FIG. 14



FIG. 15




FIG. 16




FIG. 17