



US00D341105S

United States Patent [19]

[11] Patent Number: **Des. 341,105**

Lovato

[45] Date of Patent: **** Nov. 9, 1993**

[54] **BUCKLE**

[75] Inventor: **Attilio Lovato, Pino Torinese, Italy**

[73] Assignee: **ITW Fastex Italia, S.p.A., Turin, Italy**

[**] Term: **14 Years**

[21] Appl. No.: **792,067**

[22] Filed: **Nov. 14, 1991**

[30] **Foreign Application Priority Data**

May 17, 1991 [IT] Italy T091 o 000120

[52] U.S. Cl. **D11/216; D11/218**

[58] Field of Search **D11/200, 215-218, D11/212; 24/633 A, 631, 616, 200, 197, 163 R, 196, 68 F; 297/467**

[56] **References Cited**

U.S. PATENT DOCUMENTS

- D. 300,614 4/1989 Geldwerth D11/216
- D. 303,233 8/1989 Jang D11/216
- D. 312,430 11/1990 Crowle D11/216

Primary Examiner—A. Hugo Word
Assistant Examiner—R. Seifert
Attorney, Agent, or Firm—Schwartz & Weinrieb


[57] **CLAIM**

The ornamental design for a buckle, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a first element or component of a buckle showing my new design;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a right side elevational view thereof;
FIG. 4 is a left side elevational view thereof;
FIG. 5 is a bottom plan view thereof;

FIG. 6 is a rear elevational view thereof;
FIG. 7 is a bottom plan view of a second element or component of the two-piece snap-engagement type buckle clasp mechanism showing my new design;
FIG. 8 is a front elevational view of the second element or component of FIG. 7;
FIG. 9 is a left side elevational view of the second element or component of FIG. 7;
FIG. 10 is a right side elevational view of the second element or component of FIG. 7;
FIG. 11 is a top plan view of the second element or component of FIG. 7;
FIG. 12 is a rear elevational view of the second element or component of FIG. 7;
FIG. 13 is a left side elevational view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together;
FIG. 14 is a front elevational view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together as shown in FIG. 13;
FIG. 15 is a top plan view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together as shown in FIG. 13;
FIG. 16 is a rear elevational view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together as shown in FIG. 13;
FIG. 17 is a bottom plan view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together as shown in FIG. 13; and,
FIG. 18 is a right side elevational view of the two-piece snap-engagement type buckle clasp mechanism with the first and second elements or components thereof connected together as shown in FIG. 13.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 8




Fig. 7




Fig. 9




Fig. 10




Fig. 11




Fig. 12






Fig. 13

Fig. 14 Fig. 15






Fig. 16




Fig. 17

Fig. 18

