



US00D342411S

# United States Patent [19]

[11] Patent Number: **Des. 342,411**

**Graebe**

[45] Date of Patent: **\*\* Dec. 21, 1993**

[54] SEAT CUSHION

[76] Inventor: **Robert H. Graebe**, 7 Persimmon Ridge Dr., Belleville, Ill. 62223

[\*\*] Term: **14 Years**

[21] Appl. No.: **1,439**

[22] Filed: **Nov. 13, 1992**

4,893,873 1/1990 Iwamoto et al. .... 297/452

4,953,913 9/1990 Graebe ..... 297/459

5,018,790 5/1991 Jay ..... 297/458

5,052,068 10/1991 Graebe .

5,079,790 1/1992 Pouch ..... 5/431

5,163,737 11/1992 Navach et al. .... 297/459

### Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 839,305, Feb. 20, 1992, abandoned.

[52] U.S. Cl. .... **D6/601; D6/596**

[58] Field of Search ..... **D6/595, 596, 601, 604; 5/654, 653; 297/459, DIG. 1**

### FOREIGN PATENT DOCUMENTS

1030500 6/1953 France ..... 5/468

### OTHER PUBLICATIONS

Tri-Max Information sheet D-8083 dated Jan. 1, 1989.

*Primary Examiner*—Wallace R. Burke  
*Assistant Examiner*—Lisa Lichtenstein  
*Attorney, Agent, or Firm*—Polster, Lieder, Woodruff & Lucchesi

### References Cited

#### U.S. PATENT DOCUMENTS

D. 335,235 5/1993 Hildreth ..... D6/601

2,800,165 7/1957 Talalay et al. .... 297/DIG. 1

2,970,638 2/1961 Halter ..... 297/456

3,376,070 4/1968 Johnson ..... 297/459

4,164,798 8/1979 Weber ..... 5/464

4,424,599 1/1984 Hannouche ..... 5/636

4,541,136 9/1985 Graebe ..... 5/456

4,643,481 2/1987 Saloff et al. .... 297/458

4,682,818 7/1987 Morell ..... 297/452

4,698,864 10/1987 Graebe ..... 5/441

4,726,624 2/1988 Jay ..... 297/459

4,753,480 6/1988 Morell ..... 297/452

4,796,948 1/1989 Paul et al. .... 297/284

4,809,374 3/1989 Saviez ..... 5/420


4,866,800 9/1989 Bedford ..... 5/468

### [57] CLAIM

The ornamental design for a seat cushion, as shown and described.

### DESCRIPTION

FIG. 1 is a top perspective view of the seat cushion of this invention;  
 FIG. 2 is a right side elevational view and the left side view is identical;  
 FIG. 3 is a bottom plan view of one embodiment of the invention;  
 FIG. 4 is a front elevational view of the invention;  
 FIG. 5 is a rear elevational view of the invention; and,  
 FIG. 6 is a bottom perspective view of a second embodiment of the invention, the top, side and rear views being identical to FIGS. 1, 2, 4 and 5.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6